

Synergy Telecom P Ltd.

Part No.- ATCB-DB9-005-COMP

AISG RET CONTROL CABLE - AISG FEMALE TO DB9 MALE



Key Features

- ✓ Compatible with AISG connectors
- ✓ Outdoor IP67 compliant
- ✓ Flame retardant, Polyurethane jacket
- ✓ Up to 100% humidity

Applications

- ✓ Remote Electrical Tilt (RET) applications
- ✓ AISG compliant antenna control units
- ✓ Tower mount amplifiers with AISG interface
- ✓ Control Network interfaces with AISG interface

Specifications

- ✓ Braid: Tinned copper
- ✓ Outer Jacket: Black PVC A
- ✓ Dimensions: 2 x 0.25 sq. mm (24 AWG) twisted pair with 4 x 0.75 sq. mm (20 AWG) stranded

WZ-47, Saini Chowk, Budella, Vikaspuri, New Delhi-110018
Phone-91-11-28533349, Mobile-91 98101 38894, Fax-91 11 2853-1435
E-mail: Pradeep@rfconnectorhouse.com, Website: <http://www.rfconnector.info/>

Synergy Telecom P Ltd.

Electrical specification

| | |
|----------------------|------------------------|
| Rating | Up to 300 V max |
| Complies with | CB /CE |

Mechanical Characteristics

| | |
|------------------------------------|--|
| AISG Connector A | 8-pin DIN Female |
| AISG Connector A Body Style | Straight |
| AISG Connector A Standard | IEC 60130-9 |
| Connector B | 9-pin D-sub Male |
| Data Conductor Type | 0.24 mm² (24 AWG) twisted pair |
| Power Conductor Type | 0.82 mm² (18 AWG) stranded |
| Jacket | Flame retardant, Polyurethane |

Environmental Specification

| | |
|--------------------------|---|
| Temperature Range | -40 °C to +70 °C (-40 °F to +158 °F) |
| Weatherproof Rate | IP67 |

WZ-47, Saini Chowk, Budella, Vikaspuri, New Delhi-110018
Phone-91-11-28533349, Mobile-91 98101 38894, Fax-91 11 2853-1435
E-mail: Pradeep@rfconnectorhouse.com, Website: <http://www.rfconnector.info/>