



L9 Female BT 3002 Cable:-



1.6/5.6 Connector Female

Electrical		
Characteristic impedance		50 ohm
Frequency range		DC-3GHz
VSWR		≤1.1
Contact resistance	inner conductor:	< 1.0mΩ
	outer conductor:	< 0.25 mΩ
Dielectric withstanding voltage		> 2500V RMS, 50Hz, at sea level
Dielectric resistance		> 5000MΩ
Mechanical		
Mating cycles		> 500
Material and plating		
	Material	plating
Body	Brass	Gold
Insulator	Teflon	-
Center conductor	Brass	Gold
Coupling nut	Brass	
Environmental		
Temperature range		-40°C ~ +85°C
Drafted by:		Approved by:


SYNERGY TELECOM (P) LTD.
 13-15, RP5 Flats, E-Block, Vasant Puri, New Delhi - 110 018 (INDIA)
 Phone: +91-11-28533349 Fax: +91-11-28531435 Mobile: +91-9810138894
 Email: pradeep@rfconnectorhouse.com, MSN: pradeepagrowalsynergy@hotmail.com
 PRINCIPAL SITE: <http://www.vinncom.info> Skype Account: pradeepag
 My trademanager ID: synergytelecom www.rfconnectors.info

pdfMachine
Is a pdf writer that produces quality PDF files with ease!
 Produce quality PDF files in seconds and preserve the integrity of your original documents. Compatible across nearly all Windows platforms, if you can print from a windows application you can use pdfMachine.
 Get yours now!