Synergy Telecom P Ltd.

Torque Wrench N and SMA Connector



Standard style torque spanners as well as box spanners for applications with high packing densities are

| Type Item no. | | For Series | Torque(NM) | Opening | |
|---------------|------------|--------------|------------|----------------|--|
| CHB-0-0-21 | BS22543130 | SMA/PC 3.5 | 1.00 | 8.0mm/.315 in. | |
| CHB-0-0-45 | BS22543232 | SMC | 0.35 | 6.0mm/.236 in. | |
| CHB-0-0-79 | BS22642374 | SMA economic | 0.46 | 8.0mm/.315 in. | |
| CHB-0-0-80 | BS22544821 | SMA hermetic | 1.95 | 7.0mm/.276 in. | |
| CHB-0-0-174 | BS22643898 | SK | 1.30 | 8.0mm/.315 in. | |
| CHB-0-0-189 | BS22644368 | SKhermetic | 2.00 | 8.0mm/.315 in. | |
| CHB-0-0-192 | BS22645084 | TNC | 1.00 | 15.0mm/.591 in | |
| CHB-0-0-193 | BS22645085 | N | 1.00 | 20.0mm/.787 in | |
| CHB-0-0-321 | BS22651994 | N | 1.00 | 19.0mm/.748 in | |
| CHB-0-0-330 | BS22658130 | N | 1.00 | 18.0mm/.709 in | |
| CHB-0-0-373 | BS23021864 | TNC | 1.00 | 14.0mm/.551 in | |

Torque Wrenches





| | Order No. | for Series | Torque | AF (across flats) | Notes |
|--------------|-----------|--------------|---------|--------------------------|-------------|
| 74 Z-0-0-21 | 22543130 | SMA / PC 3.5 | 1.00 Nm | 8.0 mm/. <i>315 in</i> | |
| 74 Z-0-0-45 | 22544232 | SMC | 0.35 Nm | 6.0 mm/.236 in. | |
| 74 Z-0-0-77 | 22544820 | SMA | 1.00 Nm | 8.0 mm/. <i>315 in</i> . | box-spanner |
| 74 Z-0-0-78 | 22641379 | SMA economic | 0.45 Nm | 8.0 mm/. <i>315 in</i> . | box-spanner |
| 74 Z-0-0-79 | 22642374 | SMA economic | 0.45 Nm | 8.0 mm/. <i>315 in</i> . | |
| 74 Z-0-0-80 | 22544821 | SMA hermetic | 1.95 Nm | 7.0 mm/.276 in. | 1 |
| 74 Z-0-0-147 | 22644235 | SMC | 0.35 Nm | 6.0 mm/.236 in. | box-spanner |

13-15 RPS flats, E-block, Vikaspuri, N Delhi-110018, India Phone-91 11 28533349, Mobile-91 98101 38894, Fax -91 11 2853 1435, E-mail: pradeep@rfconnectorhouse.com, Website: http://www.rfconnector.info/