


S. NO.	Connectors	PART NO.	DESCRIPTION	IMAGES
1	DIN F 1-1/4" LDF CLAMP	ST02DINF114LDFCL06	Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ Operating Temp - -40°C~+85°C	
2	DIN F 1/2" LDF CLAMP	ST02DINF12LDFCL06	Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ Operating Temp - -40°C~+85°C	
3	DIN F 1/2" LDF SOLDER	ST02DINF12LDFS06	Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ Operating Temp - -40°C~+85°C	
4	DIN F 1/2" SF CLAMP	ST02DINF12SFCL06	Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ Operating Temp - -40°C~+85°C	
5	DIN F 1/2" SF SOLDER	ST02DINF12SFS06	Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ Operating Temp - -40°C~+85°C	
6	DIN F 4 HOLE 1/4" CLAMP	ST02DINF4H14LDFCL06	Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ Operating Temp - -40°C~+85°C	
7	DIN F 4 HOLE RG 141 SOLDER	ST02DINF4H141S06	Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ Operating Temp - -40°C~+85°C	
8	DIN F 4 HOLE SM 250 SOLDER	ST02DINF4H250S06	Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ Operating Temp - -40°C~+85°C	

9	DIN F 4 HOLE SOLDER	ST02DINF4HS06	<p>Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
10	DIN F 7/8" AL CLAMP	ST02DINF78ALCL06	<p>Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
11	DIN F 7/8" CLAMP	ST02DINF78CL06	<p>Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
12	DIN F BH LMR 400 CRIMP	ST02DINFBH400CR06	<p>Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
13	DIN F BH RA LMR 200 CRIMP	ST02NFBHRA200CR06	<p>Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
14	DIN F LMR 400 CRIMP	ST02DINF400CR06	<p>Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
15	DIN M 1/2" LDF CLAMP	ST02DINM12LDFCL06	<p>Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
16	DIN M 1/2" LDF SOLDER	ST02DINM12LDFS06	<p>Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	

17	DIN M 1/2" SF CLAMP	ST02DINM12SFCL06	<p>Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
18	DIN M 1/2" SF SOLDER	ST02DINM12SFS06	<p>Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
19	DIN M 1/4" SF CLAMP	ST02DINM14SFCL06	<p>Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
20	DIN M 1/4" SF SOLDER	ST02DINM14SFS06	<p>Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
21	DIN M 1-5/8" LDF CLAMP	ST02DINM158LDFCL06	<p>Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
22	DIN M 4 HOLE SOLDER	ST02DINM4HS06	<p>Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
23	DIN M 7/8" AL CLAMP	ST02DINM78ALCL06	<p>Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
24	DIN M 7/8" CLAMP	ST02DINM78CL06	<p>Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	

25	DIN M LMR 400 CRIMP	ST02DINM400CR06	<p>Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
26	DIN M LMR 200 CRIMP	ST02DINM200CR06	<p>Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
27	DIN M RA 1/2" LDF CLAMP	ST02DINMRA12LDFCL06	<p>Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
28	DIN M R/A 1/2" LDF SOLDER	ST02DINMRA12LDFS06	<p>Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
29	DIN M RA 1/2" SF CLAMP	ST02DINMRA12SFCL06	<p>Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
30	DIN M RA 1/2" SF SOLDER	ST02DINMRA12SFS06	<p>Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
31	DIN M RA 1/4" SF CLAMP	ST02DINMRA14SFCL06	<p>Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
32	DIN M RA LMR 400 CRIMP	ST02DINMRA400CR06	<p>Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	

33	MINI DIN F 1/2" SF CLAMP	ST02MDINF12SFCL06	<p>Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ Operating Temp - -40°C~+85°C</p>	
34	MINI DIN M 1/2" SF SOLDER	ST02MDINM12SFS06	<p>Impedan - 50Ω Frequency - 6.5Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ Operating Temp - -40°C~+85°C</p>	