



















S. NO.	2.92mm Connectors (DC-40Ghz)	PART NO.	DESCRIPTION	IMAGES
1	2.92mm Series Field Replaceable Flange Connectors	ST02292F4H40	<p>Impedan - 50Ω</p> <p>Frequency - DC~40Ghz</p> <p>VSWR - 1.15:1 (Max)</p> <p>Contact resistance - Conductor ≤ 3.0mΩ Outer Conductors≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
2	2.92mm Series Field Replaceable Flange Connectors	ST02292F4H40	<p>Impedan - 50Ω</p> <p>Frequency - DC~40Ghz</p> <p>VSWR - 1.15:1 (Max)</p> <p>Contact resistance - Conductor ≤ 3.0mΩ Outer Conductors≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
3	2.92mm Series Field Replaceable Flange Connectors	ST02292FSD40	<p>Impedan - 50Ω</p> <p>Frequency - DC~40Ghz</p> <p>VSWR - 1.15:1 (Max)</p> <p>Contact resistance - Conductor ≤ 3.0mΩ Outer Conductors≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
4	2.92mm Series Field Replaceable Flange Connectors	ST02292M4H40	<p>Impedan - 50Ω</p> <p>Frequency - DC~40Ghz</p> <p>VSWR - 1.15:1 (Max)</p> <p>Contact resistance - Conductor ≤ 3.0mΩ Outer Conductor≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
5	2.92mm Series Field Replaceable Flange Connectors	ST02292M2H40	<p>Impedan - 50Ω</p> <p>Frequency - DC~40Ghz</p> <p>VSWR - 1.15:1 (Max)</p> <p>Contact resistance - Conductor ≤ 3.0mΩ Outer Conductors≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
6	2.92mm Series Bulkhead Flange Connectors	ST02292F4H40	<p>Impedan - 50Ω</p> <p>Frequency - DC~40Ghz</p> <p>VSWR - 1.15:1 (Max)</p> <p>Contact resistance - Conductor ≤ 3.0mΩ Outer Conductors≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
7	2.92mm Series Bulkhead Flange Connectors	ST02292F2H40	<p>Impedan - 50Ω</p> <p>Frequency - DC~40Ghz</p> <p>VSWR - 1.15:1 (Max)</p> <p>Contact resistance - Conductor ≤ 3.0mΩ Outer Conductors≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
8	2.92mm Series Thread-in Connectors	ST02292F4H40	<p>Impedan - 50Ω</p> <p>Frequency - DC~40Ghz</p> <p>VSWR - 1.15:1 (Max)</p> <p>Contact resistance - Conductor ≤ 3.0mΩ Outer Conductor≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
9	2.92mm Series Thread-in Connectors	ST02292F2H40	<p>Impedan - 50Ω</p> <p>Frequency - DC~40Ghz</p> <p>VSWR - 1.15:1 (Max)</p> <p>Contact resistance - Conductor ≤ 3.0mΩ Outer Conductors≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	

10	2.92mm Series Airline Bulkhead connectors	ST02292F4H40	<p>Impedan - 50Ω</p> <p>Frequency - DC~40Ghz</p> <p>VSWR - 1.15:1 (Max)</p> <p>Contact resistance - Conductor ≤ 3.0mΩ Outer Conductor≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
11	2.92mm Series Airline Bulkhead connectors	ST02292F4H40	<p>Impedan - 50Ω</p> <p>Frequency - DC~40Ghz</p> <p>VSWR - 1.15:1 (Max)</p> <p>Contact resistance - Conductor ≤ 3.0mΩ Outer Conductor≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
12	2.92mm Series Airline Bulkhead connectors	ST02292M4H40	<p>Impedan - 50Ω</p> <p>Frequency - DC~40Ghz</p> <p>VSWR - 1.15:1 (Max)</p> <p>Contact resistance - Conductor ≤ 3.0mΩ Outer Conductor≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
13	2.92mm Series Airline Bulkhead connectors	ST02292M2H40	<p>Impedan - 50Ω</p> <p>Frequency - DC~40Ghz</p> <p>VSWR - 1.15:1 (Max)</p> <p>Contact resistance - Conductor ≤ 3.0mΩ Outer Conductor≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
14	2.92mm Series PCB Connectors	ST02292MPCB40	<p>Impedan - 50Ω</p> <p>Frequency - DC~40Ghz</p> <p>VSWR - 1.15:1 (Max)</p> <p>Contact resistance - Conductor ≤ 3.0mΩ Outer Conductor≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
15	2.92mm Series PCB Connectors	ST02292MPCB40	<p>Impedan - 50Ω</p> <p>Frequency - DC~40Ghz</p> <p>VSWR - 1.15:1 (Max)</p> <p>Contact resistance - Conductor ≤ 3.0mΩ Outer Conductor≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
16	2.92mm Series Bulkhead Thread-in Connectors	ST02292MBH40	<p>Impedan - 50Ω</p> <p>Frequency - DC~40Ghz</p> <p>VSWR - 1.15:1 (Max)</p> <p>Contact resistance - Conductor ≤ 3.0mΩ Outer Conductor≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
S. NO.	2.4mm Connectors (DC-50Ghz)	PART NO.	DESCRIPTION	IMAGES
17	2.4mm Series Field Replaceable Flange Connectors	ST0224F4H50	<p>Impedan - 50Ω</p> <p>Frequency - DC~50Ghz</p> <p>VSWR - 1.15:1 (Max)</p> <p>Contact resistance - Conductor ≤ 3.0mΩ Outer Conductor≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
18	2.4mm Series Field Replaceable Flange Connectors	ST0224F4H50	<p>Impedan - 50Ω</p> <p>Frequency - DC~50Ghz</p> <p>VSWR - 1.15:1 (Max)</p> <p>Contact resistance - Conductor ≤ 3.0mΩ Outer Conductor≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	

19	2.4mm Series Field Replaceable Flange Connectors	ST0224F4H50	<p>Impedan - 50Ω Frequency - DC~50Ghz VSWR - 1.15:1 (Max) Contact resistance - Conductor ≤ 3.0mΩ Outer Conductors≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
20	2.4mm Series Field Replaceable Flange Connectors	ST0224M4H50	<p>Impedan - 50Ω Frequency - DC~50Ghz VSWR - 1.15:1 (Max) Contact resistance - Conductor ≤ 3.0mΩ Outer Conductors≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
21	2.4mm Series Field Replaceable Flange Connectors	ST0224M4H50	<p>Impedan - 50Ω Frequency - DC~50Ghz VSWR - 1.15:1 (Max) Contact resistance - Conductor ≤ 3.0mΩ Outer Conductors≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
22	2.4mm Series Bulkhead Flange Connectors	ST0224F4H50	<p>Impedan - 50Ω Frequency - DC~50Ghz VSWR - 1.15:1 (Max) Contact resistance - Conductor ≤ 3.0mΩ Outer Conductors≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
23	2.4mm Series Bulkhead Flange Connectors	ST0224F2H50	<p>Impedan - 50Ω Frequency - DC~50Ghz VSWR - 1.15:1 (Max) Contact resistance - Conductor ≤ 3.0mΩ Outer Conductors≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
24	2.4mm Series Thread-in Connectors	ST0224F4H50	<p>Impedan - 50Ω Frequency - DC~50Ghz VSWR - 1.15:1 (Max) Contact resistance - Conductor ≤ 3.0mΩ Outer Conductor≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
25	2.4mm Series Thread-in Connectors	ST0224F2H50	<p>Impedan - 50Ω Frequency - DC~50Ghz VSWR - 1.15:1 (Max) Contact resistance - Conductor ≤ 3.0mΩ Outer Conductors≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
26	2.4mm Series Airline Bulkhead Connectors	ST0224F4H50	<p>Impedan - 50Ω Frequency - DC~50Ghz VSWR - 1.15:1 (Max) Contact resistance - Conductor ≤ 3.0mΩ Outer Conductors≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
27	2.4mm Series Airline Bulkhead Connectors	ST0224F2H50	<p>Impedan - 50Ω Frequency - DC~50Ghz VSWR - 1.15:1 (Max) Contact resistance - Conductor ≤ 3.0mΩ Outer Conductors≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	

28	2.4mm Series Airline Bulkhead Connectors	ST0224M4H50	<p>Impedan - 50Ω Frequency - DC~50Ghz VSWR - 1.15:1 (Max) Contact resistance - Conductor ≤ 3.0mΩ Outer Conductors≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
29	2.4mm Series Airline Bulkhead Connectors	ST0224M2H50	<p>Impedan - 50Ω Frequency - DC~50Ghz VSWR - 1.15:1 (Max) Contact resistance - Conductor ≤ 3.0mΩ Outer Conductors≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
S. NO.	1.85mm Connectors	PART NO.	DESCRIPTION	IMAGES
30	1.85mm Series Field Replaceable Flange Connectors	ST02185F4H65	<p>Impedan - 50Ω Frequency - DC~65Ghz VSWR - 1.25:1 (Max) Contact resistance - Conductor ≤ 3.0mΩ Outer Conductors≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
31	1.85mm Series Field Replaceable Flange Connectors	ST02185F2H65	<p>Impedan - 50Ω Frequency - DC~65Ghz VSWR - 1.25:1 (Max) Contact resistance - Conductor ≤ 3.0mΩ Outer Conductor≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
32	1.85mm Series Field Replaceable Flange Connectors	ST02185F2H65	<p>Impedan - 50Ω Frequency - DC~65Ghz VSWR - 1.25:1 (Max) Contact resistance - Conductor ≤ 3.0mΩ Outer Conductors≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
33	1.85mm Series Field Replaceable Flange Connectors	ST02185FSD65	<p>Impedan - 50Ω Frequency - DC~65Ghz VSWR - 1.25:1 (Max) Contact resistance - Conductor ≤ 3.0mΩ Outer Conductors≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
34	1.85mm Series Field Replaceable Flange Connectors	ST02185FSD65	<p>Impedan - 50Ω Frequency - DC~65Ghz VSWR - 1.25:1 (Max) Contact resistance - Conductor ≤ 3.0mΩ Outer Conductors≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
35	1.85mm Series Field Replaceable Flange Connectors	ST02185M4H65	<p>Impedan - 50Ω Frequency - DC~65Ghz VSWR - 1.25:1 (Max) Contact resistance - Conductor ≤ 3.0mΩ Outer Conductor≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	
36	1.85mm Series Field Replaceable Flange Connectors	ST02185M2H65	<p>Impedan - 50Ω Frequency - DC~65Ghz VSWR - 1.25:1 (Max) Contact resistance - Conductor ≤ 3.0mΩ Outer Conductors≤2.5mΩ</p> <p>Operating Temperature - -55°C~+165°C</p>	

37

1.85mm Series Field Replaceable
Flange Connectors

ST02185M2H65

Impedan - 50Ω
Frequency - DC~65Ghz
VSWR - 1.25:1 (Max)
Contact resistance - Conductor \leq
 $3.0m\Omega$ Outer Conductors $\leq 2.5m\Omega$
Operating Temperature - $-55^{\circ}\text{C}\sim+165^{\circ}\text{C}$

