


S. NO.	Jumper Cable	PART NO.	DESCRIPTION	IMAGES
1	DIN M to DIN M with 1/2" S.F Jumper Cable 3Mtr	ST01DINMM12SF3M075	Frequency - DC-7.5Ghz Impedance - 50Ohm VSWR - 1.5 Max. Power - 100watt Cable - 1/2" S.F Connector A - DIN M Connector B - DIN M Cable Length - 3Mtr Operating Temp - -40°C~+85°C	
2	DIN M to DIN F with 1/2" S.F Jumper Cable 3Mtr	ST01DINMF12SF3M075	Frequency - DC-7.5Ghz Impedance - 50Ohm VSWR - 1.5 Max. Power - 100watt Cable - 1/2" S.F Connector A - DIN M Connector B - DIN F Cable Length - 3Mtr Operating Temp - -40°C~+85°C	
3	N M to N M with 1/2" S.F Jumper Cable 3Mtr	ST01NMM12SF3M075	Frequency - DC-7.5Ghz Impedance - 50Ohm VSWR - 1.5 Max. Power - 100watt Cable - 1/2" S.F Connector A - N M Connector B - N M Cable Length - 3Mtr Operating Temp - -40°C~+85°C	
4	N M to N F with 1/2" S.F Jumper Cable 3Mtr	ST01NMF12SF3M075	Frequency - DC-7.5Ghz Impedance - 50Ohm VSWR - 1.5 Max. Power - 100watt Cable - 1/2" S.F Connector A - N M Connector B - N F Cable Length - 3Mtr Operating Temp - -40°C~+85°C	
5	Mini DIN M to Mini DIN M with 1/2" S.F Jumper Cable 3Mtr	ST01MDINMM12SF3M075	Frequency - DC-7.5Ghz Impedance - 50Ohm VSWR - 1.5 Max. Power - 100watt Cable - 1/2" S.F Connector A - Mini DIN M Connector B - Mini DIN M Cable Length - 3Mtr Operating Temp - -40°C~+85°C	
6	Mini DIN M to Mini DIN F with 1/2" S.F Jumper Cable 3Mtr	ST01MDINMF12SF3M075	Frequency - DC-7.5Ghz Impedance - 50Ohm VSWR - 1.5 Max. Power - 100watt Cable - 1/2" S.F Connector A - Mini DIN M Connector B - Mini DIN F Cable Length - 3Mtr Operating Temp - -40°C~+85°C	
7	DIN M to MINI DIN M with 1/2" S.F Jumper Cable 3Mtr	ST01DINMDINMM12SF3M075	Frequency - DC-7.5Ghz Impedance - 50Ohm VSWR - 1.5 Max. Power - 100watt Cable - 1/2" S.F Connector A - DIN M Connector B - Mini DIN M Cable Length - 3Mtr Operating Temp - -40°C~+85°C	

8	DIN M to N M with 1/2" S.F Jumper Cable 3Mtr	ST01DINNMM12SF3M075	<p>Frequency - DC-7.5Ghz          Impedance - 50Ohm          VSWR - 1.5          Max. Power - 100watt          Cable - 1/2" S.F          Connector A - DIN M          Connector B - N M          Cable Length - 3Mtr          Operating Temp - -40°C~+85°C</p>	
9	Mini DIN M to N M with 1/2" S.F Jumper Cable 3Mtr	ST01MDINNMM12SF3M075	<p>Frequency - DC-7.5Ghz          Impedance - 50Ohm          VSWR - 1.5          Max. Power - 100watt          Cable - 1/2" S.F          Connector A - DIN M          Connector B - N M          Cable Length - 3Mtr          Operating Temp - -40°C~+85°C</p>	