



## 6 meter Manual Telescopic Mast

|                        |                     |
|------------------------|---------------------|
| Height of each section | 1700 mm             |
| Top tube size          | 40 mm <sup>2</sup>  |
| Second tube size       | 50 mm <sup>2</sup>  |
| Third tube size        | 60 mm <sup>2</sup>  |
| Fourth tube size       | 72 mm <sup>2</sup>  |
| Fifth tube size        | 100 mm <sup>2</sup> |
| Base tube              | 125 mm <sup>2</sup> |
| Thickness              | 2 mm                |
| Retreated Height       | 2.4 mm              |

|                   |                            |
|-------------------|----------------------------|
| Part Number       | ST-06M-MWM-HW              |
| Retracted height  | < 2 Meter                  |
| Extended height   | 6 meter                    |
| Material          | Mild Steel                 |
| Application       | Outdoor                    |
| Lifting method    | Manual Winch               |
| Shape             | Square Tube                |
| Section           | 4 Sections                 |
| Locking Method    | Self Locking at any Height |
| Wind Resistance   | 8 Grade                    |
| Top Spigot/Flange | Included                   |
| Colour            | Military Green/Custom      |



### Special Feature

Guy wire support is also available as an option for our mast, providing enhanced wind protection and stability. All masts are manufactured using advanced laser cutting machines for high-end accuracy and perfect fit of each component.