









Items	Products Descriptions	Pictures	PRICE
Module	<p>Frequency: 420-470MHz Power supply: DC 24-28V Output power($\pm 0.5dBm$): 50dBm Output Power:95-100w Operating Temperature: -20°C ~65°C RF PORT: Output: N-female Shell Size: 177*102*27 mm, Net Weight: 0.9kg Control Voltage 28V</p>		40,000
Module	<p>Frequency: 860-930MHz Power supply: DC 24-28V Output power($\pm 0.5dBm$): 50dBm Output Power:95-100w Operating Temperature: -20°C ~65°C RF PORT: Output: N-female Shell Size: 177*102*27 mm, Net Weight: 0.9kg Control Voltage 28V</p>		40,000
Module	<p>Frequency: 1170-1280MHz Power supply: DC 24-28V Output power($\pm 0.5dBm$): 50dBm Output Power:95-100w Operating Temperature: -20°C ~65°C RF PORT: Output: N-female Shell Size: 177*102*27 mm, Net Weight: 0.9kg Control Voltage 28V</p>		40,000
Module	<p>Frequency: 1560-1620MHz Power supply: DC 24-28V Output power($\pm 0.5dBm$): 50dBm Output Power:95-100w Operating Temperature: -20°C ~65°C RF PORT: Output: N-female Shell Size: 177*102*27 mm Net Weight: 0.9kg Control Voltage 28V</p>		40,000
Module	<p>Frequency: 2400-2500MHz Power supply: DC 24-28V Output power($\pm 0.5dBm$): 50dBm Output Power:95-100w Operating Temperature: -20°C ~65°C RF PORT: Output: N-female Shell Size: 177*102*27 mm Net Weight: 0.9kg Control Voltage 28V</p>		40,000
Module	<p>Frequency: 5100-5300MHz Power supply:DC 24-28V Output power($\pm 0.5dBm$): 51dBm Output Power:95-100w Operating Temperature: -20°C ~65°C RF PORT: Output: N Shell Size: 170*60*24mm Net Weight:0.489 kg Control Voltage 28V</p>		200,000
Module	<p>Frequency: 5400-5700MHz Power supply:DC 24-28V Output power($\pm 0.5dBm$): 51dBm Output Power:95-100w Operating Temperature: -20°C ~65°C RF PORT: Output: N Shell Size: 170*60*24mm Net Weight:0.489 kg Control Voltage 28V</p>		200,000
Module	<p>Frequency: 5700-5900MHz Power supply:DC 24-28V Output power($\pm 0.5dBm$): 51dBm Output Power:95-100w Operating Temperature: -20°C ~65°C RF PORT: Output: N Shell Size: 170*60*24mm Net Weight:0.489 kg Control Voltage 28V</p>		200,000