














S. NO.	Connectors	PART NO.	DESCRIPTION	IMAGES
1	SMA F 2 HOLE SOLDER	ST02SMAF2HS06	Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - $\geq 5000M\Omega$ Contact Resistance - Center Contact $\leq 3m\Omega$ Outer Contact $\leq 2.5m\Omega$ Operating Temp - $-40^{\circ}C \sim +85^{\circ}C$	
2	SMA F 4 HOLE RG .86 SOLDER	ST02SMAF4H86S06	Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - $\geq 5000M\Omega$ Contact Resistance - Center Contact $\leq 3m\Omega$ Outer Contact $\leq 2.5m\Omega$ Operating Temp - $-40^{\circ}C \sim +85^{\circ}C$	
3	SMA F 4 HOLE RG 141 SOLDER	ST02SMAF4H141S06	Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - $\geq 5000M\Omega$ Contact Resistance - Center Contact $\leq 3m\Omega$ Outer Contact $\leq 2.5m\Omega$ Operating Temp - $-40^{\circ}C \sim +85^{\circ}C$	
4	SMA F 4 HOLE SOLDER	ST02SMAF4HS06	Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - $\geq 5000M\Omega$ Contact Resistance - Center Contact $\leq 3m\Omega$ Outer Contact $\leq 2.5m\Omega$ Operating Temp - $-40^{\circ}C \sim +85^{\circ}C$	
5	SMA F BH LMR 100 CRIMP	ST02SMAFBH100CR06	Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - $\geq 5000M\Omega$ Contact Resistance - Center Contact $\leq 3m\Omega$ Outer Contact $\leq 2.5m\Omega$ Operating Temp - $-40^{\circ}C \sim +85^{\circ}C$	
6	SMA F BH RA PCB SOLDER	ST02SMAFBHRAS06	Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - $\geq 5000M\Omega$ Contact Resistance - Center Contact $\leq 3m\Omega$ Outer Contact $\leq 2.5m\Omega$ Operating Temp - $-40^{\circ}C \sim +85^{\circ}C$	
7	SMA F BH RG 141 SOLDER	ST02SMAFBH141S06	Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - $\geq 5000M\Omega$ Contact Resistance - Center Contact $\leq 3m\Omega$ Outer Contact $\leq 2.5m\Omega$ Operating Temp - $-40^{\circ}C \sim +85^{\circ}C$	
8	SMA F BH RG 178 CPS	ST02SMAFBH178CPS06	Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - $\geq 5000M\Omega$ Contact Resistance - Center Contact $\leq 3m\Omega$ Outer Contact $\leq 2.5m\Omega$ Operating Temp - $-40^{\circ}C \sim +85^{\circ}C$	


9	SMA F BH SOLDER LONG THREAD	ST02SMAFBHSLT06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
10	SMA F EDGE MOUNT PCB SOLDER	ST02SMAFEMPS06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
11	SMA F LMR 200 CRIMP	ST02SMAF200CR06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
12	SMA F PCB SMD SOLDER	ST02SMAFMSDS06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
13	SMA F PCB SOLDER	ST02SMAFPCBS06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
14	SMA F RA PCB SOLDER	ST02SMAFRAS06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
15	SMA F RA RP PCB SOLDER	ST02SMAFRARPS06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
16	SMA F RG .86 SOLDER	ST02SMAF086S06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	

17	SMA F RP LMR 100 CRIMP	ST02SMAFRP100CR06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
18	SMA F RP LMR 200 CRIMP	ST02SMAFRP200CR06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
19	SMA F RP PCB SOLDER	ST02SMAFRPPS06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
20	SMA F SM 250 SOLDER	ST0SMAF250S06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
21	SMA M 1/2" SF CLAMP	ST02SMAM12SFCL06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
22	SMA M 2 HOLE SOLDER	ST02SMAM2HS06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
23	SMA M 4 HOLE SOLDER	ST02SMAM4HS06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
24	SMA M BT 3002 CRIMP	ST02SMAM3002CR06	<p>Impedan - 75Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	

25	SMA M LMR 100 CLAMP	ST02SMAM100CL06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
26	SMA M LMR 100 CRIMP	ST02SMAM100CR06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
27	SMA M LMR 200 CRIMP	ST02SMAM200CR06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
29	SMA M LMR 300 CRIMP	ST02SMAM300CR06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
30	SMA M LMR 400 CRIMP	ST02SMAM400CR06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
31	SMA M PCB SOLDER	ST02SMAMPCBS06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
32	SMA M RA LMR 100 CLAMP	ST02SMAMRA100CL06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
33	SMA M RA LMR 100 CRIMP	ST02SMAMRA100CR06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	

34	SMA M RA LMR 200 CRIMP	ST02SMARA200CR06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
35	SMA M RA LMR 400 CLAMP	ST02SMAMRA400CL06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
36	SMA M RA LMR 400 CRIMP	ST02SMAMRA400CR06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
37	SMA M RA PCB SOLDER	ST02SMAMRAPCBS06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
38	SMA M RA RG 141 SOLDER	ST02SMAMRA141S06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
39	SMA M RA RG 59 CRIMP	ST02SMAMRA59CR06	<p>Impedan - 75Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
40	SMA M RA RG .86 SOLDER	ST02SMAMRA08606	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
41	SMA M RA RP LMR 200 CRIMP	ST02SMAMRARP200CR06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	

42	SMA M RG 141 SOLDER	ST02SMAM141S06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
43	SMA M RA RG 59 CRIMP	ST02SMAMRA59CR06	<p>Impedan - 75Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
44	SMA M RA RG .86 SOLDER	ST02SMAMRA86S06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
45	SMA M RA RP LMR 200 CRIMP	ST02SMAMRARP200CR06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
46	SMA M RG 59 CRIMP	ST02SMAM5906	<p>Impedan - 75Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
47	SMA M RG .86 SOLDER	ST02SMAM086S06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
48	SMA M RP LMR 100 CRIMP	ST02SMAMRP100CR06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	
49	SMA M RP LMR 200 CRIMP	ST02SMAMRP200CR06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ</p> <p>Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ</p> <p>Operating Temp - -40°C~+85°C</p>	

50	SMA M RP RG 141 SOLDER	ST02SMAMRP141S06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ Operating Temp - -40°C~+85°C</p>	
51	SMA M SM 250 SOLDER	ST02SMAM250S06	<p>Impedan - 50Ω Frequency - 4Ghz VSWR - 1.15:1 (Max) Dielectric Resistance - ≥5000MΩ Contact Resistance - Center Contact ≤3mΩ Outer Contact ≤2.5mΩ Operating Temp - -40°C~+85°C</p>	