



Corrugated cable 3/8" (Cellflex 3/8" Spiral)



P/N: ST291 996 170
(Cellflex HCF 3/8" CuH-50 AlCu)

APPLICATION NOTE

The outer conductor of this cable is made up of a corrugated tube (spiral winding). This construction allows perfect shielding and bendability while enabling large bending radius.

The foam dielectric provides excellent loss and low return loss levels.

This cable is suitable for feeder and jumper assemblies in cellular networks as well as applications requiring high performance level on long distances.

The anti-UV LSZH (Low Smoke Zero Halogen) material is also flame retardant and allows this cable to be used for indoor public areas as well as outdoor installations.

CONSTRUCTION / DIMENSIONS

	Material	mm	Inches
Center conductor	Solid AlCC ⁽¹⁾	2.60	0.102
Dielectric	Foam PE ⁽²⁾	6.30	0.248
Corrugated inner shield	Spiral copper tube	9.10	0.358
Outer shield	-	-	-
Jacket	Black LSZH PE ⁽³⁾	10.20	0.402

ELECTRICAL CHARACTERISTICS

Characteristic impedance	50Ω ± 1Ω	
Operating frequency range	DC - 13.4 GHz	
Shielding effectiveness	110 dB	
Voltage withstanding	4 500 V rms	
Peak power	11.9 kW	
Capacitance	82 pF / m	24.8 pF / ft
Velocity of propagation	82 % (4.1 ns / m)	