

[1] SPC: Silver Plated Copper

Cable	VP	Max Dia.	Attenuation	Bending radius	Weight
SHF2.4M DC - 40GHz	78%	2.45mm 0.096in.	4,68 dB/m @40GHz 139 dB/100ft	10 mm 0.394 in.	20 g/m 6.1 g/ft
SHF2.9M [2] DC - 87GHz	75%	2.90mm 0.114in.	6.82 dB/m @87GHz 172 dB/100ft	25 mm 0.984 in.	23 g/m 7.01 g/ft
SHF3M DC - 40GHz	78%	3.64mm 0.139in.	2.78 dB/m @40GHz 84 dB/100ft	12.5 mm 0.492 in.	36 g/m 10.5 g/ft
SHF4M [2] DC - 40GHz	84%	4.15mm 0.160in.	2.06 dB/m @40GHz 62 dB/100ft	20 mm 0.788 in.	40 g/m 12.2 g/ft
SHF4.2M DC - 28.6GHz	78%	4.20mm 0.165in.	1.88 dB/m @28.6GHz 60 dB/100ft	25 mm 0.984 in.	45 g/m 13.6 g/ft
SHF5M DC - 28.6GHz	84%	5.20mm 0.201in.	1,27 dB/m @28.6GHz 39 dB/100ft	25 mm 0.984 in.	60 g/m 18.2 g/ft
SHF8M DC - 18GHz	84%	7.78mm 0.302in.	0,68 dB/m @18GHz 21 dB/100ft	40 mm 1.575 in.	130 g/m 39.4g/ft
SHF13 DC - 8.6GHz	85%	13.80mm 0.543in.	0,33 dB/m @8.5GHz 9 dB/100ft	80 mm 2.362 in.	280 g/m 84.8 g/ft

[2] Triple shield structure

Stranded inner conductor cable



Using stranded center conductor allow better flexibility while keeping good IL performance level

Longer flex life

SHF3, SHF5, SHF8

Ultra Flexible cable



Unique design of center conductor as well as braiding and jacketing provide a unique flexibility behavior to SHF UF

SHF2.2UF, SHF3UF, SHF5UF

Armored cable



In many customer applications mechanical stress may damage cable assemblies. Radiall has designed several levels of armored structures embedding SHF core lines.

SHF5PJ, SHF8PJ

LSZH Outdoor cable



Designed to be used in outdoor environments, Radiall's OutDoor cables are typically chosen for Ground Radars and Navy systems.
Halogen free jacket according to IEC60754-1

SHF5MZH, SHF8MZH

Light Weight & Air Frame cable



Radiall's LightWeight range is the best choice for on-board equipements, where weight and density are critical.
SHF AirFrame cables moto is: Robustness for long life in extreme condition. Radiall's AirFrame cables are used in non-pressurized or not-protected areas.

30% weight saving
Hermetically sealed
16 Km (50,000 ft) - 160°C
Fluid resistant

SHF5MLW-2, SHF8MLW-2
SHF5MAF-2, SHF8MAF-2

TestPro cables



Radiall full range of test bench cables provides outstanding performances and durability.
Radiall Test cables are the perfect solution for component/ assembly shops, labs, automatic test equipments and test benches

Excellent Stability
Long durability

TestPro4.2S, TestPro4.2
TestPro3, TestPro3 Low Profile
TestPro2, TestPro VNA

Space qualified cable



To resist to the extreme conditions in space, Space qualified range includes several jacket material options. Our cable radiation resistance is up to 80Mrads with Fluorinated ethylene propylene (FEP) jackets, whilst ETFE version resist to more than 120Mrads.

Ultra-light -weight
Non-outgassing materials
High radiation resistance

SHF2.4MS, SHF5MS, SHF8MS
SHF3MS, SHF4.8MS (eTFE jacketed)