Mob: +91 7217885948 www.rfconnector.in pradeeep@rfconnector.in

Contents

CABLE ASSEMBLIES
Introduction 18-4
Specify the right cable for your application 18-5
Finder guide cables vs insertion loss . .... 18-6 to 18-7

FLEXIBLE CABLES (STANDARD)
0.8/50 S cable (132390 type) 18-8
1/50 S cable (50VMTX type) 18-8
1/75 S cable (75VMTX type) 18-9
2/50 S cable (RG178-KX21A-RG178 non mag) . .... 18-9 to 18-10
2/50 D cable (124416 type) 18-10
2/75 S cable (296775 type) 18-11
2.6/50 S cable (RG174-KX3B-RG316-KX22A) .... 18-11 to 18-12
2.6/50 D cable (RD316) 18-12
2.6/75 S cable (RG179). 18-13
4.6/75 D cable (HD 0.6/2.8-mini RG59 type) 18-13
5/50 S cable (RG58-KX15) 18-14
5/50 D cable (RG142-RG223-RG400-KX23) . .... 18-14 to 18-16
6/75 S cable (RG59-KX6A). .... 18-16 to 18-17
6/75 D cable (HD 0.8/3.7-RG59 type) 18-17
7/75 D cable (HD 1.0/4.8-RG6 type) 18-18
10/50 S cable (RG213-KX4) 18-18
10/50 D cable (RG393) 18-19
11/50 D cable (RG214-KX13) 18-19
11/75 D cable (RG216) 18-20

FLEXIBLE CABLES (LOW-LOSS ECO-FRIENDLY)
2.6/50 S cable (ECO316-ECO316X) .... 18-20 to 18-21
2.6/50 D cable (ECO316D-ECO316DX) . .... 18-21 to 18-22
5/50 D cable (ECO142-ECO142X-Power142) .... 18-22 to 18-23
6/50 D cable (ECO230) 18-24
10/50 D cable (ECO393-ECO393X) .... 18-24 to 18-25

CORRUGATED CABLES
Cable 1/4" spiral (HCF 1/4"-50 AlCu) 18-25
Cable 3/8" spiral (HCF 3/8" CuH-50 AlCu) 18-26
Cable 1/2" spiral (HCF 1/2" CuH-50 AlCu) 18-26

SEMI-RIGID AND HAND-FORMABLE CABLES
.047" cable (SR copper-SR tinned copper) 18-27
.085" cable (Handformable unjacketed-SR RG405/KS1-SR tinned copper-SR non magnetic-SR aluminum). ... 18-28 to 18-30
.141" cable (Handformable unjacketed-Handformable FEP jacketed-SR RG402/KS2
SR tinned copper-SR silvered copper-SR non magnetic-SR aluminum) .... 18-30 to 18-33
.250" cable (SR RG401/KS3-SR aluminum) 18-34

LOW-LOSS FLEXIBLE CABLES
AEP-100FR (LMR® 100) 18-35
AEP-195FR (LMR® 195) 18-36
AEP-200FR (LMR® 200) 18-37
AEP-240FR (LMR® 240) 18-38
AEP-400FR (LMR® 400) 18-39
AEP-600FR (LMR® 600) 18-40

SHF ULTRA LOW LOSS CABLES . .... 18-41 to 18-44

Radiall cable groups

Example for flexible cables: 5/50 S
- **Cable outer diameter in mm** (2.6 mm, 5 mm, 10 mm, 11 mm,...)
- **Characteristic impedance** (50Ω, 75Ω)
- **Number of shields** (S=single, D=double)

Example for corrugated cables: 1/2 spiral
- **Cable outer conductor diameter in fraction of inch** (1/4", 3/8", 1/2",...)

Example for semi-rigid & handformable cables: .141"
- **Cable outer conductor diameter in inches** (.085", .141", .250",...)

Plot no. 845, DSIIDC Industrial Area KHASRA NO. 33/23 (0-7) & 37/4 (0-10)Gali no. 6, near Harnandi dharam kanta Mundka Industrial Area, New Delhi, Delhi, 110041