



pradecp@rfconnector.in

9810138894

www.synergypnl.com

AUTO ANTENNA FEMALE CONNECTOR

High quality Auto Antenna Female Connector designed for reliable signal reception and durable automotive connectivity. Built with precision metal construction for secure fitting, corrosion resistance, and stable performance. Ideal for car antenna, vehicle electronics, and communication applications.



SECURE MOUNTING

Flange mounting design ensures stable and firm installation.



HIGH PERFORMANCE

Provides dependable signal connectivity with low loss.



DURABLE CONSTRUCTION

Metal body offers long service life and corrosion resistance.



EASY INSTALLATION

Simple fitment for automotive antenna assemblies.



WIDE COMPATIBILITY

Suitable for car antenna, automotive audio and related systems.

SPECIFICATIONS

Product Name	Auto Antenna Female Connector
Connector Type	Auto Antenna Female
Mounting Type	Flange / Panel Mount
Contact Material	Brass (Nickel Plated)
Body Material	Brass / Steel (Nickel Plated)
Insulator Material	PTFE
Impedance	50 Ω
Frequency Range	DC – 300 MHz
Voltage Rating	12 V DC
Contact Resistance	≤ 20 m Ω
Insulation Resistance	≥ 1000 M Ω
Operating Temperature	-20°C to +70°C
Application	Car Antenna, Automotive, Communication Systems
RoHS Compliant	Yes

APPLICATIONS



Car Antennas



Automotive Audio Systems



Vehicle Electronics



Communication Systems



RF Systems



Industrial Applications



QUALITY ASSURED

Tested for performance and long-term reliability.



BUILT FOR PRECISION

Engineered with high accuracy and standards.



RELIABLE & SAFE

Ensures stable connectivity and safe operation.



CUSTOMER SUPPORT

Dedicated support for all your needs.



pradeep@rfconnector.in



9810138894



www.synergyppl.com

P-38 MONO MALE CONNECTOR HEAVY DUTY (C.P.) W/SPRING FULLY GP



High quality P-38 Mono Male Connector Heavy Duty with spring for strain relief and long life. Fully Gold Plated (GP) contacts ensure excellent conductivity and corrosion resistance. Ideal for audio, RF and general electronic applications.



HEAVY DUTY DESIGN

Robust construction for long-lasting performance in demanding applications.



SPRING STRAIN RELIEF

Spring design protects the cable from bending and increases durability.



FULLY GOLD PLATED

Fully gold plated (GP) contacts provide excellent conductivity and corrosion resistance.



SECURE CONNECTION

Precision engineered for secure and stable signal transmission.



WIDE APPLICATION

Suitable for audio, RF and general electronic applications.

SPECIFICATIONS

Product Name	P-38 Mono Male Connector Heavy Duty (C.P.) W/Spring Fully GP
Connector Type	P-38 Mono Male
Contact Material	Brass (Gold Plated)
Plating	Fully Gold Plated (GP)
Body Material	Brass (Gold Plated)
Insulator Material	POM / PVC
Spring	Steel (Gold Plated)
Impedance	50 Ω
Voltage Rating	30 V DC
Dielectric Withstanding Voltage	500 V RMS
Contact Resistance	≤ 20 m Ω
Insulation Resistance	≥ 1000 M Ω
Operating Temperature	-20°C to +70°C
Application	Audio, RF, Test Equipment, Electronic Applications
RoHS Compliant	Yes

APPLICATIONS



Audio Systems



RF Applications



PA & Sound Systems



Test Equipment



Electronic Devices



General Electronic Applications



QUALITY ASSURED

Tested for high performance and reliability



BUILT FOR PRECISION

Accurate connections for critical applications



RELIABLE & SAFE

Designed for repeated and safe use



CUSTOMER SUPPORT

Dedicated support for all your technical needs



pradecp@rfconnector.in 9810138894 www.synergytpl.com

P-38 MONO MALE CONNECTOR HEAVY DUTY (C.P.) W/SPRING FULLY GP



High quality P-38 Mono Male Connector Heavy Duty with spring for strain relief and long life. Fully Gold Plated (GP) contacts ensure excellent conductivity and corrosion resistance. Ideal for audio, RF and general electronic applications.



1. HEAVY DUTY DESIGN

Robust construction for long-lasting performance in demanding applications.



2. SPRING STRAIN RELIEF

Spring design protects the cable from bending and increases durability.



3. FULLY GOLD PLATED

Fully gold plated contacts provide excellent conductivity and corrosion resistance.



4. SECURE CONNECTION

Precision engineered for secure and stable signal transmission.



5. WIDE APPLICATION

Suitable for audio, RF and general electronic applications.

SPECIFICATIONS

Product Name	P-38 Mono Male Connector Heavy Duty (C.P.) W/Spring Fully GP
Connector Type	P-38 Mono Male
Contact Material	Brass (Gold Plated)
Plating	Fully Gold Plated (GP)
Body Material	Brass (Gold Plated)
Insulator Material	POM / PVC
Spring	Steel (Gold Plated)
Impedance	50 Ω
Voltage Rating	30 V DC
Dielectric Withstanding Voltage	500 V RMS
Contact Resistance	≤ 20 m Ω
Insulation Resistance	≥ 1000 M Ω
Operating Temperature	-20°C to +70°C
Application	Audio, RF, Test Equipment, Electronic Applications
RoHS Compliant	Yes

APPLICATIONS



Audio Systems



RF Applications



PA & Sound Systems



Test Equipment



Electronic Devices



General Electronic Applications



PREMIUM QUALITY

High quality materials for reliable performance



RELIABLE PERFORMANCE

Engineered for secure and stable connections



TECHNICAL SUPPORT

Expert support for all your requirements



CUSTOMER SATISFACTION

Committed to quality and customer trust



pradeep@rfconnector.in



9810138894



www.synergypcl.com

P-38 ST MALE / 2 EP ST FEMALE CONNECTOR



High quality P-38 ST Male to 2 EP ST Female Connector for professional audio applications. Designed for reliable and stable signal transmission with excellent sound quality. Durable construction ensures long life and consistent performance.



STEREO COMPATIBLE

P-38 Stereo Male to 2 EP Stereo Female for versatile audio connections.



HIGH QUALITY SOUND

Ensures clear and stable audio transmission with minimal signal loss.



DURABLE CONSTRUCTION

Robust design with high quality materials for long lasting performance.



SECURE CONNECTION

Precision engineered connectors ensure tight and stable connections.



WIDE APPLICATION

Ideal for audio equipment, mixers, amplifiers, and other professional setups.

SPECIFICATIONS

Product Name	P-38 ST Male / 2 EP ST Female Connector
Connector Type	P-38 Stereo Male to 2 EP Stereo Female
Contact Material	Brass (Nickel Plated)
Insulator Material	POM / PVC
Body Material	ABS
Plating	Nickel Plated
Configuration	P-38 ST Male to 2 EP ST Female
Impedance	50 Ω
Voltage Rating	30 V DC
Dielectric Withstanding Voltage	500 V RMS
Contact Resistance	≤ 20 m Ω
Insulation Resistance	≥ 1000 M Ω
Operating Temperature	-20°C to +70°C
Application	Audio, PA Systems, Mixers, Amplifiers, Professional Audio
RoHS Compliant	Yes

APPLICATIONS



Audio Systems



Mixers



Amplifiers



Studio Equipment



PA Systems



QUALITY ASSURED
Tested for high performance and reliability



BUILT FOR PRECISION
Accurate connections for critical applications



RELIABLE & SAFE
Designed for repeated and safe use



CUSTOMER SUPPORT
Dedicated support for all your technical needs



CUSTOMER SUPPORT
Dedicated support for all
your technical needs



pradecp@rfconnector.in

9810138894

www.synergyppl.com

4mm BANANA MALE CONNECTOR S.D. (C.P.) BERYLLIUM COPPER (BC)

This high-quality 4mm banana male connector features S.D. (C.P.) construction with beryllium copper (BC) contact, ensuring excellent conductivity, durability, and secure electrical connections. Ideal for test, audio, laboratory, power-supply, and general electrical applications.



HIGH CONDUCTIVITY

Beryllium copper (BC) contact ensures excellent electrical conductivity and minimal signal loss.



SHOCKPROOF DESIGN

Insulated PVC body provides protection against accidental shocks and short circuits.



SECURE CONNECTION

Precision-engineered 4mm banana male plug for tight, stable, and reliable connections.



DURABLE CONSTRUCTION

Robust build with high-quality materials for long-lasting performance in demanding environments.



EASY INSTALLATION

Solder / screw connection type ensures quick and easy installation for various applications.

COLORS AVAILABLE



SPECIFICATIONS

Product Name:	4mm Banana Male Connector S.D. (C.P.) Beryllium Copper (BC)
Connector Type:	4mm Banana Male
Contact Material:	Beryllium Copper (BC)
Body Material:	PVC / Metal
Finish / Plating:	Silver or Nickel Plated Contact
Insulator Material:	PVC
Rated Current:	24 A (Max.)
Rated Voltage:	60 V DC (Max.)
Contact Resistance:	$\leq 10 \text{ m}\Omega$
Insulation Resistance:	$\geq 1000 \text{ M}\Omega$
Temperature Range:	-20°C to $+80^{\circ}\text{C}$
Connection Type:	Solder / Screw
Application:	Test Equipment, Audio Systems, Power Supplies, Laboratory Use, General Electrical
RoHS Compliant:	Yes

APPLICATIONS



Audio Systems



Test Equipment



Laboratory Use



Power Supplies



Educational Use



General Electrical Applications



PREMIUM QUALITY
High-grade materials for reliable performance



RELIABLE & DURABLE
Built for long-lasting use in demanding conditions



EASY TO INSTALL
User-friendly design for quick & secure setup



TECHNICAL SUPPORT
Expert assistance for all your connectivity needs



pradeep@rfconnector.in



9810138894



www.synergyppl.com

BNC MALE CONNECTOR F.M. (C.P.) (PIN G.P.)



High quality BNC Male Connector Female Mate (C.P.), Pin Gold Plated (G.P.) for reliable and stable signal transmission. Designed for professional RF, test and measurement applications.



SECURE CONNECTION

Precision machined for secure and stable connection.



HIGH PERFORMANCE

Ensures excellent signal transmission with low insertion loss.



DURABLE CONSTRUCTION

Nickel plated body for high strength, durability and corrosion resistance.



GOLD PLATED PIN

Pin Gold Plated (G.P.) for superior conductivity and long life.



EASY INSTALLATION

Easy to assemble and suitable for various RF applications.



SPECIFICATIONS

Product Name	BNC Male Connector F.M. (C.P.) (Pin G.P.)
Connector Type	BNC Male (Female Mate)
Contact Material	Brass (Pin Gold Plated)
Body Material	Brass (Nickel Plated)
Insulator Material	PTFE / Delrin
Plating	Nickel Plated (Body) Gold Plated (Pin)
Impedance	50 Ω
Frequency Range	DC - 4 GHz
Voltage Rating	500 V RMS
Dielectric Withstanding Voltage	1500 V RMS
Contact Resistance	≤ 10 m Ω
Insulation Resistance	≥ 5000 M Ω
VSWR	≤ 1.3 (up to 2 GHz)
Operating Temperature	-40°C to +85°C
Application	RF, Test & Measurement, Communication, Instrumentation, Broadcast, CCTV
RoHS Compliant	Yes

APPLICATIONS



RF & Wireless Systems



Test & Measurement



Communication Equipment



Broadcast Systems



CCTV & Surveillance



Industrial Applications



QUALITY ASSURED
Tested for high performance and reliability



BUILT FOR PRECISION
Accurate connections for critical applications



RELIABLE & SAFE
Designed for repeated and safe use



CUSTOMER SUPPORT
Dedicated support for all your technical needs



pradeep@rfconnector.in

9810138894

www.synergytpl.com

RCA MALE CONNECTOR F.M. (C.P.)

RCA Male Connector F.M. (C.P.) is designed for reliable audio, video, and RF signal transmission. It ensures stable connectivity, low signal loss, and excellent performance. Built with durable materials and corrosion resistance, it offers long-lasting reliability and easy installation for professional and consumer applications.



HIGH PERFORMANCE

Ensures reliable signal transmission with low loss and high efficiency.



DURABLE CONSTRUCTION

Nickel plated brass body for superior strength, durability and reliability.



SECURE CONNECTION

Precision engineered design for stable and secure connectivity.



WIDE COMPATIBILITY

Compatible with audio, video and RF equipment with RCA ports.



EASY INSTALLATION

Simple plug and play design ensures quick and hassle-free installation.

SPECIFICATIONS

Product Name	RCA Male Connector F.M. (C.P.)
Connector Type	RCA Male
Design	F.M. (C.P.)
Contact Material	Brass (Nickel Plated)
Body Material	Brass (Nickel Plated)
Insulator Material	PTFE / POM
Impedance	75 Ω
Frequency Range	0 – 3 GHz
Voltage Rating	250 V RMS
Contact Resistance	≤ 20 m Ω
Insulation Resistance	≥ 1000 M Ω
Operating Temperature	-20°C to +70°C
Application	Audio, Video, RF Applications
RoHS Compliant	Yes

APPLICATIONS



Audio
Systems



Video
Systems



Communication
Equipment



Test &
Measurement



Broadcasting
Systems



Consumer
Electronics



QUALITY ASSURED

Tested for high performance and reliability



BUILT FOR PRECISION

Accurate connections for critical applications



RELIABLE & SAFE

Designed for repeated and safe use



CUSTOMER SUPPORT

Dedicated support for all your technical needs



pradeep@rfconnector.in

9810138894

www.synergytpl.com

RCA MALE CONNECTOR F.M. (C.P.)

RCA Male Connector F.M. (C.P.) is designed for reliable audio, video, and RF signal transmission. It ensures stable connectivity, low signal loss, and excellent performance. Built with durable materials and corrosion resistance, it offers long-lasting reliability and easy installation for professional and consumer applications.



HIGH PERFORMANCE

Ensures reliable signal transmission with low loss and high efficiency.



DURABLE CONSTRUCTION

Nickel plated brass body for superior strength, durability and reliability.



SECURE CONNECTION

Precision engineered design for stable and secure connectivity.



WIDE COMPATIBILITY

Compatible with audio, video and RF equipment with RCA ports.



EASY INSTALLATION

Simple plug and play design ensures quick and hassle-free installation.

SPECIFICATIONS

Product Name	RCA Male Connector F.M. (C.P.)
Connector Type	RCA Male
Design	F.M. (C.P.)
Contact Material	Brass (Nickel Plated)
Body Material	Brass (Nickel Plated)
Insulator Material	PTFE / POM
Impedance	75 Ω
Frequency Range	0 – 3 GHz
Voltage Rating	250 V RMS
Contact Resistance	≤ 20 m Ω
Insulation Resistance	≥ 1000 M Ω
Operating Temperature	-20°C to +70°C
Application	Audio, Video, RF Applications
RoHS Compliant	Yes

APPLICATIONS



Audio
Systems



Video
Systems



Communication
Equipment



Test &
Measurement



Broadcasting
Systems



Consumer
Electronics



QUALITY ASSURED

Tested for high performance and reliability



BUILT FOR PRECISION

Accurate connections for critical applications



RELIABLE & SAFE

Designed for repeated and safe use



CUSTOMER SUPPORT

Dedicated support for all your technical needs



pradeep@rfconnector.in

9810138894

www.synergypnl.com

RF FEMALE CONNECTOR CHASSIS F.M.

High quality RF Female Connector Chassis F.M. designed for reliable panel/chassis mounting and stable signal transmission. Built with durable metal construction for low loss performance, corrosion resistance, and long service life. Ideal for RF, communication, test, and industrial applications.



SECURE CHASSIS MOUNT

Designed for stable and firm panel installation.



HIGH PERFORMANCE

Provides dependable RF connectivity with low signal loss.



DURABLE CONSTRUCTION

Nickel plated metal body for strength and long service life.



SECURE CONNECTION

Precision interface ensures reliable contact and fit.



WIDE COMPATIBILITY

Suitable for RF, communication, and electronic equipment.

SPECIFICATIONS

Product Name	RF Female Connector Chassis F.M.
Connector Type	RF Female
Design	Chassis F.M.
Mounting Type	Chassis / Panel Mount
Contact Material	Brass (Nickel Plated)
Body Material	Brass / Steel (Nickel Plated)
Insulator Material	PTFE
Impedance	50 Ω
Frequency Range	DC - 3 GHz
Voltage Rating	250 V RMS
Contact Resistance	≤ 20 m Ω
Insulation Resistance	≥ 1000 M Ω
Operating Temperature	-20°C to +70°C
Application	RF Applications, Communication, Test Equipment
RoHS Compliant	Yes

APPLICATIONS



RF Systems



Communication Equipment



Test & Measurement



Broadcasting Systems



Network Devices



Industrial Applications



QUALITY ASSURED

Premium materials and strict quality control.



BUILT FOR PRECISION

Engineered for accuracy, consistency and reliability.



RELIABLE & SAFE

Tested for performance and long-term durability.



CUSTOMER SUPPORT

Dedicated support for all your requirements.



pradeep@rfconnector.in

9810138894

www.synergyppl.com

RF FEMALE CONNECTOR CHASSIS PLASTIC (FLAME RETARDANT)

High quality RF Female Connector Chassis Plastic (Flame Retardant) designed for reliable panel mounting and stable RF signal transmission. Built with durable flame-retardant plastic and precision metal contact parts for secure fitting, low loss performance, and long service life. Ideal for RF, communication, testing, and electronic equipment applications.



SPECIFICATIONS

Product Name	RF Female Connector Chassis Plastic (Flame Retardant)
Connector Type	RF Female
Design	Chassis Plastic (Flame Retardant)
Mounting Type	Chassis / Panel Mount
Contact Material	Brass (Nickel Plated)
Body Material	Flame Retardant Plastic / Metal
Insulator Material	PTFE
Impedance	50 Ω
Frequency Range	DC – 3 GHz
Voltage Rating	250 V RMS
Contact Resistance	≤ 20 m Ω
Insulation Resistance	≥ 1000 M Ω
Operating Temperature	-20°C to +70°C
Application	RF Applications, Communication, Test Equipment
RoHS Compliant	Yes



FLAME RETARDANT BODY

Flame-retardant plastic construction for improved safety and durability.



SECURE CHASSIS MOUNT

Flange mounting design ensures firm and stable installation.



HIGH PERFORMANCE

Provides dependable RF connectivity with low signal loss.



DURABLE CONSTRUCTION

Robust mixed plastic and metal structure for long service life.



WIDE COMPATIBILITY

Suitable for RF systems, communication devices, and electronic equipment.

APPLICATIONS



RF Systems



Communication
Equipment



Test &
Measurement



Broadcasting
Systems



Network
Devices



Industrial
Applications



QUALITY
ASSURED



BUILT FOR
PRECISION



RELIABLE &
SAFE



CUSTOMER
SUPPORT



pradeep@rfconnector.in



9810138894



www.synergyppl.com

BNC FEMALE CONNECTOR W/TEFLON PANEL MNTG. (PIN G.P.)



High quality BNC Female Connector with Teflon Panel Mounting and Pin Gold Plated (G.P.) contact for reliable signal transmission. Designed for easy panel installation and secure connection in RF and communication applications.



TEFLON PANEL MOUNT

Teflon insulator ensures excellent dielectric strength and durability.



SECURE CONNECTION

Precision BNC interface for stable and reliable RF signal transmission.



GOLD PLATED PIN

Pin Gold Plated (G.P.) contact provides superior conductivity and corrosion resistance.



EASY PANEL INSTALLATION

Flange mount design allows quick and secure panel mounting.



WIDE APPLICATION

Ideal for RF, communication, test equipment and industrial applications.



SPECIFICATIONS

Product Name	BNC Female Connector w/Teflon Panel Mntg. (Pin G.P.)
Connector Type	BNC Female (Panel Mount)
Contact Material	Brass (Gold Plated)
Insulator Material	Teflon (PTFE)
Body Material	Brass (Nickel Plated)
Plating	Nickel Plated (Body) Gold Plated (Pin)
Impedance	50 Ω
Frequency Range	DC – 4 GHz
Voltage Rating	500 V RMS
Dielectric Withstanding Voltage	1500 V RMS
Contact Resistance	$\leq 10 \text{ m}\Omega$
Insulation Resistance	$\geq 5000 \text{ M}\Omega$
VSWR	≤ 1.3 (up to 2 GHz)
Operating Temperature	-40°C to +85°C
Mounting Type	Panel Mount (Flange)
Application	RF, Communication, Test Equipment, Instrumentation, Broadcast
RoHS Compliant	Yes

APPLICATIONS



RF & Wireless Systems



Test & Measurement



Communication Equipment



Broadcast Systems



Industrial Applications



CCTV & Surveillance



QUALITY ASSURED

Tested for high performance and reliability



BUILT FOR PRECISION

Accurate connections for critical applications



RELIABLE & SAFE

Designed for repeated and safe use



CUSTOMER SUPPORT

Dedicated support for all your technical needs



pradeep@rfconnector.in



9810138894



www.synergyppl.com

EP ST MALE / P-38 ST FEMALE CONNECTOR METAL (G.P.)



High quality EP ST Male to P-38 ST Female Connector with Gold Plated (G.P.) finish for excellent conductivity and corrosion resistance.
Ideal for audio, RF and general electronic applications.



GOLD PLATED FINISH

Gold Plated (G.P.) contacts ensure excellent conductivity and long lasting performance.



DURABLE METAL BODY

Robust metal body provides high strength, durability and corrosion resistance.



SECURE CONNECTION

Precision engineered for secure and stable signal transmission.



EASY TO USE

Compact and easy to connect, suitable for various audio and RF applications.



WIDE APPLICATION

Ideal for audio systems, test equipment, communication and general electronics.



SPECIFICATIONS

Product Name	EP ST Male / P-38 ST Female Connector Metal (G.P.)
Connector Type	EP ST Male to P-38 ST Female
Contact Material	Brass (Gold Plated)
Plating	Gold Plated (G.P.)
Body Material	Brass (Gold Plated)
Insulator Material	PVC
Impedance	50 Ω
Frequency Range	DC – 500 MHz
Voltage Rating	30 V DC
Dielectric Withstanding Voltage	500 V RMS
Contact Resistance	$\leq 20 \text{ m}\Omega$
Insulation Resistance	$\geq 1000 \text{ M}\Omega$
Operating Temperature	-20°C to +70°C
Application	Audio, RF, Test Equipment, Communication, General Electronics
RoHS Compliant	Yes

APPLICATIONS



Audio Systems



RF Applications



Test Equipment



Communication



General Electronics



QUALITY ASSURED

Tested for high performance and reliability



BUILT FOR PRECISION

Accurate connections for critical applications



RELIABLE & SAFE

Designed for repeated and safe use



CUSTOMER SUPPORT

Dedicated support for all your technical needs



pradeep@rfconnector.in



9810138894



www.synergypnl.com

RF FEMALE CONNECTOR CHASSIS FR. MNTG.

RoHS
COMPLIANT



High quality RF Female Connector designed for chassis front mounting applications. Ensures excellent signal transmission with durable construction and secure installation. Ideal for RF equipment, test systems and communication devices.



SECURE CHASSIS MOUNT

Front mount design ensures stable and secure installation with locking nut.



EXCELLENT PERFORMANCE

Designed for reliable RF signal transmission with low loss and high efficiency.



DURABLE CONSTRUCTION

High quality metal body for strength, durability and long lasting performance.



WIDE COMPATIBILITY

Suitable for various RF systems, test equipment and communication applications.



EASY INSTALLATION

Simple front panel mounting with nut and washer for quick and secure setup.

SPECIFICATIONS

Product Name	RF Female Connector Chassis Fr. Mntg.
Connector Type	RF Female (Front Mount)
Mounting Type	Chassis Front Mount
Body Material	Brass (Nickel Plated)
Insulator Material	PTFE
Contact Material	Brass (Gold Plated)
Impedance	50 Ω
Frequency Range	DC - 3 GHz
Voltage Rating	500 V RMS
Dielectric Withstanding Voltage	1500 V RMS
Contact Resistance	≤ 10 m Ω
Insulation Resistance	≥ 5000 M Ω
VSWR	≤ 1.3 (up to 2 GHz)
Operating Temperature	-40°C to +85°C
Mounting	Front Panel Mount with Nut & Washer
Application	RF Equipment, Test Systems, Communication Devices, Instruments
RoHS Compliant	Yes

APPLICATIONS



RF Equipment



Test Systems



Communication
Devices



Measurement
Instruments



Broadcast
Systems



Industrial
Applications



QUALITY ASSURED

Tested for high performance and reliability



BUILT FOR PRECISION

Accurate connections for critical applications



RELIABLE & SAFE

Designed for repeated and safe use



CUSTOMER SUPPORT

Dedicated support for all your technical needs



pradeep@rfconnector.in



9810138894



www.synergypnl.com

RF MALE CONNECTOR CHASSIS H.M.



High quality RF Male Connector designed for chassis mounting with high mechanical strength. Ensures reliable signal transmission in RF equipment, test systems and communication devices.



SECURE CHASSIS MOUNT

Flange mount design ensures stable and secure installation with screws.



HIGH PERFORMANCE

Provides excellent RF signal transmission with low insertion loss and high reliability.



DURABLE CONSTRUCTION

Robust metal body for high strength, durability and corrosion resistance.



WIDE COMPATIBILITY

Suitable for various RF systems, test equipment and industrial applications.



EASY INSTALLATION

Simple chassis mounting with flange for quick and secure setup.

SPECIFICATIONS

Product Name	RF Male Connector Chassis H.M.
Connector Type	RF Male (Chassis Mount)
Mounting Type	Chassis Mount (Flange)
Body Material	Brass (Nickel Plated)
Insulator Material	PTFE
Contact Material	Brass (Gold Plated)
Impedance	50 Ω
Frequency Range	DC – 3 GHz
Voltage Rating	500 V RMS
Dielectric Withstanding Voltage	1500 V RMS
Contact Resistance	≤ 10 m Ω
Insulation Resistance	≥ 5000 M Ω
VSWR	≤ 1.3 (up to 2 GHz)
Operating Temperature	-40°C to +85°C
Mounting	Flange Mount with Screw Holes
Application	RF Equipment, Test Systems, Communication Devices, Measurement Instruments
RoHS Compliant	Yes

APPLICATIONS



RF Equipment



Test Systems



Communication Devices



Measurement Instruments



Broadcast Systems



Industrial Applications



QUALITY ASSURED

Tested for high performance and reliability



BUILT FOR PRECISION

Accurate connections for critical applications



RELIABLE & SAFE

Designed for repeated and safe use



CUSTOMER SUPPORT

Dedicated support for all your technical needs



pradecp@rfconnector.in

9810138894

www.synergyppl.com

RF FEMALE CONNECTOR CHASSIS H.M.

High quality RF Female Connector designed for chassis mounting applications. Ensures reliable signal transmission with durable construction and secure installation. Ideal for RF equipment, test systems and communication devices.



SPECIFICATIONS

Product Name	RF Female Connector Chassis H.M.
Connector Type	RF Female (Chassis Mount)
Mounting Type	Chassis Mount (Flange)
Body Material	Brass (Nickel Plated)
Insulator Material	PTFE
Contact Material	Brass (Gold Plated)
Impedance	50 Ω
Frequency Range	DC – 3 GHz
Voltage Rating	500 V RMS
Dielectric Withstanding Voltage	1500 V RMS
Contact Resistance	≤ 10 m Ω
Insulation Resistance	≥ 5000 M Ω
VSWR	≤ 1.3 (up to 2 GHz)
Operating Temperature	-40°C to +85°C
Application	RF Equipment, Test Systems, Communication Devices, Measurement Instruments
RoHS Compliant	Yes



SECURE CHASSIS MOUNT

Flange mount design ensures stable and secure installation.



EXCELLENT PERFORMANCE

Designed for reliable RF signal transmission with low loss and high efficiency.



DURABLE CONSTRUCTION

High quality metal body for strength, durability and long service life.



WIDE COMPATIBILITY

Suitable for RF systems, test equipment and communication applications.



EASY INSTALLATION

Simple chassis mounting design for quick and secure setup.

APPLICATIONS



RF Equipment



Test Systems



Communication
Devices



Measurement
Instruments



Broadcast
Systems



Industrial
Applications



QUALITY
ASSURED



BUILT FOR
PRECISION



RELIABLE
& SAFE



CUSTOMER
SUPPORT



pradeep@rfconnector.in



9810138894



www.synergyppl.com

BNC MALE CONNECTOR CLAMP TYPE W/TEFLON (RG-58/U)



High quality BNC Male Connector Clamp Type with Teflon (RG-58/U). Designed for secure cable clamp termination and excellent signal transmission in RF applications. Easy to install with durable construction and reliable performance.



CLAMP TYPE DESIGN

Clamp type termination ensures secure cable holding and easy installation.



HIGH PERFORMANCE

Ensures excellent signal transmission with low insertion loss.



TEFLON INSULATOR

Teflon insulator provides high dielectric strength and stable performance.



DURABLE CONSTRUCTION

Nickel plated body for high strength, durability and corrosion resistance.



WIDE APPLICATION

Suitable for a wide range of RF, communication and test applications.



SPECIFICATIONS

Product Name	BNC Male Connector Clamp Type w/Teflon (RG-58/U)
Connector Type	BNC Male (Clamp Type)
Compatible Cable	RG-58/U
Contact Material	Brass (Gold Plated)
Insulator Material	Teflon (PTFE)
Body Material	Brass (Nickel Plated)
Impedance	50 Ω
Frequency Range	DC – 4 GHz
Voltage Rating	500 V RMS
Dielectric Withstanding Voltage	1500 V RMS
Contact Resistance	≤ 10 m Ω
Insulation Resistance	≥ 5000 M Ω
VSWR	≤ 1.3 (up to 2 GHz)
Operating Temperature	-40°C to +85°C
Cable Fixing	Clamp Type
Application	RF, Communication, Test Equipment, Instrumentation, Broadcast, CCTV
RoHS Compliant	Yes

APPLICATIONS



RF & Wireless Systems



Test & Measurement



Communication Equipment



Broadcast Systems



CCTV & Surveillance



Industrial Applications



QUALITY ASSURED

Tested for high performance and reliability



BUILT FOR PRECISION

Accurate connections for critical applications



RELIABLE & SAFE

Designed for repeated and safe use



CUSTOMER SUPPORT

Dedicated support for all your technical needs



pradecp@rfconnector.in

9810138894

www.synergypnl.com

BNC FEMALE CONNECTOR INDUSTRIAL W/TEFLON (PIN G.P.)

High quality BNC Female Connector Industrial with Teflon insulator and gold plated pin engineered for reliable RF signal transmission. Designed for industrial and professional applications, it offers secure mounting, excellent durability, and superior corrosion resistance. Ideal for test equipment, communication systems, broadcast, and a wide range of RF applications.



INDUSTRIAL GRADE

Built for demanding industrial environments.



TEFLON INSULATOR

Teflon (PTFE) insulator for superior dielectric performance.



GOLD PLATED PIN

Gold plated pin ensures excellent conductivity and low signal loss.



SECURE CONNECTION

Threaded bulkhead mount provides a secure and stable connection.



EASY INSTALLATION

Easy to install with standard mounting hardware.

SPECIFICATIONS

Product Name	BNC Female Connector Industrial w/Teflon (Pin G.P.)
Connector Type	BNC Female
Mounting Type	Industrial / Bulkhead Mount
Contact Material	Brass (Gold Plated Pin)
Body Material	Brass (Nickel Plated)
Insulator Material	Teflon (PTFE)
Impedance	50 Ω
Frequency Range	DC - 4 GHz
Voltage Rating	500 V RMS
Dielectric Withstanding Voltage	1500 V RMS
Contact Resistance	≤ 10 m Ω
Insulation Resistance	≥ 5000 M Ω
VSWR	≤ 1.3
Operating Temperature	-40°C to +85°C
Application	RF, Communication, Test Equipment, Broadcast, Industrial
RoHS Compliant	Yes

APPLICATIONS



RF Systems



Test & Measurement



Communication Equipment



Broadcast Systems



CCTV & Surveillance



Industrial Applications



QUALITY ASSURED

Precision engineered for consistent performance.



BUILT FOR PRECISION

High quality materials for reliable RF connectivity.



RELIABLE & SAFE

Tested for durability, safety & long life.



CUSTOMER SUPPORT

Dedicated support for all your RF needs.



pradecp@rfconnector.in 9810138894 www.synergyppl.com

BNC MALE CONNECTOR CRIMPING TYPE (RG-59/U) W/BOOT

High quality BNC Male Connector Crimping Type with protective boot, designed for RG-59/U cable. Ensures reliable signal transmission, secure crimp termination, and durable performance for RF, communication, and test applications.



SECURE CRIMP DESIGN

Crimp termination provides strong cable retention and stable connectivity.



PROTECTIVE BOOT

Boot sleeve helps protect the cable entry and improves durability.



HIGH PERFORMANCE

Designed for low signal loss and reliable RF transmission.



DURABLE CONSTRUCTION

Nickel plated body offers strength and corrosion resistance.



EASY INSTALLATION

Simple assembly suitable for professional cable termination.

SPECIFICATIONS

Product Name	BNC Male Connector Crimping Type w/Boot
Connector Type	BNC Male
Cable Type	RG-59/U
Termination Type	Crimping Type
Contact Material	Brass (Gold Plated Pin)
Body Material	Brass (Nickel Plated)
Insulator Material	PTFE / Teflon
Boot Material	PVC / Rubber
Impedance	75 Ω
Frequency Range	DC – 3 GHz
Voltage Rating	500 V RMS
Dielectric Withstanding Voltage	1500 V RMS
Contact Resistance	≤ 10 m Ω
Insulation Resistance	≥ 5000 M Ω
Operating Temperature	-40°C to +85°C
Application	RF, Communication, CCTV, Test & Measurement
RoHS Compliant	Yes

APPLICATIONS





pradecp@rfconnector.in

9810138894

www.synergyppl.com

BNC FEMALE CONNECTOR W/PIN (G.P.) W/ DURLIN W/ TEFLON

A high-quality BNC female connector featuring a gold plated pin contact, Durlin and Teflon insulation for excellent electrical performance, reliable RF signal transmission, and durable construction—ideal for RF, communication, test, and broadcast applications.



GOLD PLATED PIN

Ensures excellent conductivity and signal integrity.



DURLIN INSULATION

Provides high mechanical strength and excellent dielectric properties.



TEFLON SUPPORT

Offers superior insulation and stable performance.



DURABLE CONSTRUCTION

Nickel plated brass body for corrosion resistance and long service life.



EASY INSTALLATION

Panel mount / bulkhead design for secure and quick fitting.

SPECIFICATIONS

Product Name	BNC Female Connector w/Pin (G.P.) w/ Durlin w/ Teflon
Connector Type	BNC Female
Mounting Type	Bulkhead / Panel Type
Contact Material	Brass (Gold Plated Pin)
Body Material	Brass (Nickel Plated)
Insulator Material	Durlin / Teflon
Impedance	50 Ω
Frequency Range	DC – 4 GHz
Voltage Rating	500 V RMS
Dielectric Withstanding Voltage	1500 V RMS
Contact Resistance	≤ 10 m Ω
Insulation Resistance	≥ 5000 M Ω
VSWR	≤ 1.3
Operating Temperature	-40°C to +85°C
Application	RF, Communication, Test Equipment, Broadcast
RoHS Compliant	Yes

APPLICATIONS



RF Systems



Test & Measurement



Communication Equipment



Broadcast Systems



CCTV & Surveillance



Industrial Applications



QUALITY ASSURED

High-quality materials and rigorous testing for consistent performance.



BUILT FOR PRECISION

Engineered for accurate connectivity and superior signal transmission.



RELIABLE & SAFE

Durable, low-loss design ensures reliability and safe operation.



CUSTOMER SUPPORT

Dedicated support for queries, guidance and technical assistance.



pradeep@rfconnector.in



9810138894



www.synergypnl.com

AKAI FEMALE CONNECTOR PANEL MNTG W/TEFLON PIN G.P.



High quality Akai Female Connector Panel Mounting with Teflon insulator and Gold Plated Pin. Designed for secure panel mounting applications, ensures excellent RF performance with low signal loss and high durability.



PANEL MOUNT DESIGN

Panel mount type ensures secure installation and stable mechanical connection.



TEFLON INSULATION

Teflon insulator provides excellent dielectric strength and high thermal stability.



GOLD PLATED PIN

Gold plated pin ensures superior conductivity, low contact resistance and long life.



HIGH PERFORMANCE

Designed for consistent RF performance with low insertion loss and high reliability.



EASY MOUNTING

Flange with screw holes for easy and secure panel mounting.



SPECIFICATIONS

Product Name	Akai Female Connector Panel Mntg w/Teflon Pin G.P.
Connector Type	Akai Female (Panel Mount)
Mounting Type	Panel Mount with Flange
Body Material	Brass (Nickel Plated)
Insulator Material	Teflon (PTFE)
Contact Material	Brass (Gold Plated Pin)
Impedance	50 Ω
Frequency Range	DC – 4 GHz
Voltage Rating	500 V RMS
Dielectric Withstanding Voltage	1500 V RMS
Contact Resistance	≤ 10 m Ω
Insulation Resistance	≥ 5000 M Ω
VSWR	≤ 1.3 (up to 2 GHz)
Operating Temperature	-40°C to +85°C
Mounting	Panel Mount with Screw Holes
Application	RF Equipment, Communication Systems, Test Instruments, Industrial Applications
RoHS Compliant	Yes

APPLICATIONS



RF & Wireless Systems



Test & Measurement



Communication Equipment



Broadcast Systems



Industrial Applications



Defense & Aerospace



QUALITY ASSURED

Tested for high performance and reliability



BUILT FOR PRECISION

Accurate connections for critical applications



RELIABLE & SAFE

Designed for repeated and safe use



CUSTOMER SUPPORT

Dedicated support for all your technical needs



pradecp@rfconnector.in

9810138894

www.synergystpl.com

AKAI MALE CONNECTOR W / TEFLON PIN G.P.



High quality Akai Male Connector with Teflon insulation and gold plated pin for reliable signal transmission and durable performance. Designed for secure fitting, low signal loss, corrosion resistance, and long service life. Ideal for RF, communication, audio-video, and test equipment applications.



GOLD PLATED PIN

Gold plated contact ensures excellent conductivity and corrosion resistance.



TEFLON INSULATION

PTFE/Teflon insulation offers strong dielectric performance and durability.



SECURE CONNECTION

Precision engineered design for stable and dependable connectivity.



DURABLE CONSTRUCTION

Nickel plated metal body provides long life and reliable operation.



EASY INSTALLATION

Compact plug-and-use design for quick and convenient connection.

SPECIFICATIONS

Product Name	Akai Male Connector w / Teflon Pin G.P.
Connector Type	Akai Male
Contact Material	Brass (Gold Plated Pin)
Body Material	Brass (Nickel Plated)
Insulator Material	Teflon (PTFE)
Impedance	75 Ω
Frequency Range	DC - 1 GHz
Voltage Rating	250 V RMS
Dielectric Withstanding Voltage	1000 V RMS
Contact Resistance	≤ 20 m Ω
Insulation Resistance	≥ 1000 M Ω
Operating Temperature	-20°C to +70°C
Application	RF, Communication, Audio / Video, Test Equipment
RoHS Compliant	Yes

APPLICATIONS



RF Systems



Audio Systems



Video Equipment



Communication Equipment



Test & Measurement



Industrial Applications



QUALITY ASSURED



BUILT FOR PRECISION



RELIABLE & SAFE



CUSTOMER SUPPORT




pradecp@rfconnector.in

9810138894

www.synergypnl.com

F TYPE MALE CONNECTOR W/RING F-7 FOR RG-11 CABLE

High quality F Type Male Connector with ring, designed for F-7 / RG-11 cable. Ensures secure cable termination, stable signal transmission, low loss performance and durable construction for reliable use in RF, communication, TV and coaxial cable systems.



SECURE CABLE FIT

Ensures firm and reliable connection for stable performance.



DURABLE CONSTRUCTION

Brass body with nickel plating for corrosion resistance and long life.



LOW SIGNAL LOSS

Optimized design for minimal attenuation and high efficiency.



EASY INSTALLATION

Simple and quick assembly with included lock ring.



WIDE COMPATIBILITY

Ideal for RF, communication, TV and coaxial cable applications.

SPECIFICATIONS

Product Name	F Type Male Connector w/Ring F-7 for RG-11 Cable
Connector Type	F Type Male
Cable Type	F-7 / RG-11
Accessory	Lock Ring Included
Body Material	Brass / Nickel Plated
Contact Material	Brass
Insulator Material	PTFE / Delrin
Impedance	75 Ω
Frequency Range	DC - 3 GHz
Voltage Rating	250 V RMS
Contact Resistance	≤ 20 m Ω
Insulation Resistance	≥ 1000 M Ω
Operating Temperature	-20°C to +70°C
Application	TV, CATV, RF, Communication, Coaxial Systems
RoHS Compliant	Yes

APPLICATIONS



TV SYSTEMS



CATV NETWORKS



RF SYSTEMS



COMMUNICATION EQUIPMENT



TEST & MEASUREMENT



INDUSTRIAL APPLICATIONS



QUALITY ASSURED

Strict quality control and testing for dependable performance.



BUILT FOR PRECISION

Engineered for accuracy and consistent connectivity.



RELIABLE & SAFE

High-grade materials ensure safety and long-term reliability.



CUSTOMER SUPPORT

Dedicated support for technical assistance and after-sales care.



pradeep@rfconnector.in



9810138894



www.synergytpl.com

F TYPE MALE CONNECTOR W/RING F-7 W/PIN FOR RG-11 CABLE (PIN G.P.)

High quality F Type Male Connector with ring F-7 and pin for RG-11 cable, designed for secure cable termination, stable signal transmission and low loss performance. Ideal for RF, CATV, TV, communication and coaxial cable applications.



SPECIFICATIONS

Product Name	F Type Male Connector w/Ring F-7 w/Pin for RG-11 Cable (Pin G.P.)
Connector Type	F Type Male (Crimp)
Cable Type	RG-11 Coaxial Cable
Accessory	Ring F-7, Pin (Gold Plated), Insulator
Contact Material	Brass (Gold Plated)
Body Material	Brass (Nickel Plated)
Insulator Material	PTFE
Impedance	75 Ω
Frequency Range	0 ~ 3 GHz
Voltage Rating	500 V RMS
Contact Resistance	≤ 10 m Ω
Insulation Resistance	≥ 5000 M Ω
Operating Temperature	-40°C to +85°C
Application	RF, CATV, TV, Communication, Coaxial Cable
RoHS Compliant	Yes



SECURE CABLE FIT

Ring F-7 ensures a tight and secure connection for RG-11 cables.



PIN CONTACT DESIGN

Gold plated center pin provides excellent conductivity and stable signal transfer.



DURABLE CONSTRUCTION

Premium brass body with nickel plating for corrosion resistance and long service life.



EASY INSTALLATION

Simple assembly with ring compression for quick and reliable installation.



WIDE COMPATIBILITY

Works seamlessly with RG-11 cables for RF, CATV, TV and communication systems.

APPLICATIONS



TV Systems



CATV Networks



RF Systems



Communication Equipment



Test & Measurement



Industrial Applications



QUALITY ASSURED

Tested for high performance and reliability



BUILT FOR PRECISION

Accurate connections for critical applications



RELIABLE & SAFE

Designed for repeated and safe use



CUSTOMER SUPPORT

Dedicated support for all your technical needs



pradecp@rfconnector.in

9810138894

www.synergyppl.com

ALUMINIUM-RING FOR F-7

High quality Aluminium Ring for F-7 designed for secure cable termination and reliable connector assembly. Lightweight yet durable construction offers stable fit, corrosion resistance and dependable performance for RF, CATV, TV and coaxial cable applications.



LIGHTWEIGHT DESIGN

Aluminium construction offers easy handling and installation.



SECURE FIT

Designed to provide a firm and stable grip in connector assemblies.



CORROSION RESISTANCE

Metal ring resists wear and environmental exposure.



DURABLE CONSTRUCTION

Built for dependable long-term use in cable systems.



EASY INSTALLATION

Simple shape allows quick fitting in F-7 connector setups.

SPECIFICATIONS

Product Name	Aluminium-Ring for F-7
Component Type	Ring / Lock Ring
Compatible Connector	F-7
Material	Aluminium
Finish	Natural Aluminium
Construction	Formed Metal Ring
Weight	Lightweight
Corrosion Resistance	Yes
Application	F Connector Assembly, RF, CATV, TV, Coaxial Cable
Installation	Manual Fitment
Operating Use	Indoor / General Purpose
RoHS Compliant	Yes

APPLICATIONS



RF Systems



CATV Networks



TV Systems



Communication Equipment



Coaxial Cable Assembly



Industrial Applications



QUALITY ASSURED



BUILT FOR PRECISION



RELIABLE & SAFE



CUSTOMER SUPPORT



pradeep@rfconnector.in



9810138894



www.synergyppl.com

3 PIN MIC PLUG/CONNECTOR (C.P.) W.S. (PIN G.P.)

High quality 3 pin mic plug/connector with chrome-plated body and gold-plated pin, designed for secure audio signal transmission and durable performance. Ideal for use in microphones and other audio equipment applications.



SPECIFICATIONS

Product Name	3 Pin Mic Plug/Connector (C.P.) W.S. (Pin G.P.)
Connector Type	3 Pin Mic Plug / Connector
Contact Material	Brass (Gold Plated)
Body Material	Brass (Chrome Plated)
Insulator Material	PBT
Plating	Chrome Plated Body, Gold Plated Pin
Pin Type	3 Pin (Gold Plated)
Impedance	50 Ω
Voltage Rating	250 V RMS
Contact Resistance	≤ 20 m Ω
Insulation Resistance	≥ 5000 M Ω
Operating Temperature	-20°C to +70°C
Application	Microphones, Audio & Communication Equipment
RoHS Compliant	Yes

APPLICATIONS



Audio Systems



Microphones



PA Systems



Communication Equipment



Test Equipment



Studio Applications



QUALITY ASSURED

Tested for high performance and reliability



BUILT FOR PRECISION

Accurate connections for critical applications



RELIABLE & SAFE

Designed for repeated and safe use



CUSTOMER SUPPORT

Dedicated support for all your technical needs



✉ pradeep@rfconnector.in

☎ 9810138894

🌐 www.synergypnl.com

3 PIN MIC FEMALE CONNECTOR (PIN G.P.)



High quality 3 Pin Mic Female Connector with Gold Plated Pins (G.P.), designed for secure and lasting connections in audio and communication systems. Durable build ensures excellent performance and reliability.



SECURE CONNECTION

Precision engineered design ensures a firm and stable connection.



GOLD PLATED PINS

Gold plated pins for excellent conductivity and corrosion resistance.



DURABLE CONSTRUCTION

High quality metal body for strength, durability and long service life.



EASY INSTALLATION

Panel mount design for easy installation and secure fit.



WIDE APPLICATION

Suitable for audio equipment, communication devices and industrial use.



SPECIFICATIONS

Product Name	3 Pin Mic Female Connector (Pin G.P.)
Connector Type	3 Pin Mic Female (Panel Mount)
Pin Configuration	3 Pin
Pin Material	Brass (Gold Plated)
Body Material	Brass (Nickel Plated)
Insulator Material	PBT / Bakelite
Mounting Type	Panel Mount
Termination Type	Solder Type
Contact Resistance	$\leq 10 \text{ m}\Omega$
Insulation Resistance	$\geq 1000 \text{ M}\Omega$
Withstanding Voltage	500 V AC RMS
Current Rating	5 A Max.
Operating Temperature	-20°C to +85°C
Durability	≥ 500 Cycles
Application	Audio Equipment, Microphone, Communication Systems, Industrial Use
RoHS Compliant	Yes

APPLICATIONS



Microphone Systems



Audio Equipment



Communication Devices



Broadcast Systems



Industrial Automation



AV & Consumer Electronics



QUALITY ASSURED

Tested for high performance and reliability



BUILT FOR PRECISION

Accurate connections for critical applications



RELIABLE & SAFE

Designed for repeated and safe use



CUSTOMER SUPPORT

Dedicated support for all your technical needs



pradecp@rfconnector.in

9810138894

www.synergypnl.com

10 WAY RCA FEMALE CONNECTOR

High quality 10 Way RCA Female Connector for audio and video signal distribution. Built with durable materials for reliable performance and long lasting use. Ideal for AV systems, amplifiers, home theater installations, studio setups, and professional audio-video distribution.



PREMIUM QUALITY

High grade construction ensures excellent performance and reliability.



EXCELLENT CONNECTIVITY

Designed for stable audio and video signal transmission.



DURABLE & RELIABLE

Robust build for long lasting use in various environments.



EASY INSTALLATION

Panel mount design for quick and secure installation.



WIDE APPLICATION

Ideal for audio systems, AV setups, amplifiers, and home theaters.

SPECIFICATIONS

Product Name	10 Way RCA Female Connector
Connector Type	RCA Female (Panel Mount)
No. of Channels	10 Way
Connector Color	White (5) / Red (5)
Body Material	Metal & Plastic
Panel Material	High Quality ABS
Mounting Type	Panel Mount
Contact Material	Brass (Nickel Plated)
Insulator Material	PBT
Voltage Rating	50V AC RMS
Current Rating	1A Max. per Channel
Operating Temperature	-20°C to +85°C
Application	Audio & Video Signal Distribution, Home Theater, AV Systems, Amplifiers
RoHS Compliant	Yes

APPLICATIONS



Home Theater Systems



Amplifiers



Audio & Video Distribution



Studio Equipment



Car Audio Systems



Professional AV Installations



QUALITY ASSURED



BUILT FOR PRECISION



RELIABLE & SAFE



CUSTOMER SUPPORT



✉ pradeep@rfconnector.in



9810138894



www.synergytpl.com

6 WAY RCA FEMALE CONNECTOR PCB MNTG.



High quality 6 Way RCA Female Connector PCB Mounting type, designed for reliable audio signal transmission. Durable construction ensures long-lasting performance and secure connections in audio systems, consumer electronics, and professional applications.



PREMIUM QUALITY

High quality materials ensure excellent signal transmission and durability.



SECURE CONNECTION

RCA female connectors provide stable and secure connectivity.



DURABLE CONSTRUCTION

Robust build for long-lasting performance in demanding environments.



PCB MOUNTING

Easy PCB mounting design ensures strong mechanical support and easy installation.



WIDE APPLICATION

Ideal for audio systems, home theaters, amplifiers, and consumer electronics.



SPECIFICATIONS

Product Name	6 Way RCA Female Connector PCB MNTG.
Connector Type	RCA Female
No. of Ways	6 Way (2 Rows x 3 Columns)
Mounting Type	PCB Mounting
Contact Material	Brass (Nickel Plated)
Insulator Material	PBT
Body Material	ABS
Contact Plating	Nickel Plated
RCA Color	Red (3) / White (3)
Operating Temperature	-20°C to +85°C
Application	Audio Systems, Home Theater, Amplifiers, Consumer Electronics
RoHS Compliant	Yes

APPLICATIONS



Audio Systems



Home Theater Systems



Amplifiers



Television



Speaker Systems



Consumer Electronics



QUALITY ASSURED

Tested for high performance and reliability



BUILT FOR PRECISION

Accurate connections for critical applications



RELIABLE & SAFE

Designed for repeated and safe use



CUSTOMER SUPPORT

Dedicated support for all your technical needs



pradecp@rfconnector.in

9810138894

www.synergypnl.com

RF FEMALE / F FEMALE CONNECTOR (PIN G.P.)

High quality RF Female / F Female Connector with gold plated pin contact for reliable signal transmission and secure connectivity. Built with durable metal construction for low loss, corrosion resistance, and long service life. Ideal for RF, CATV, communication and test applications.



GOLD PLATED PIN

Gold plated pin provides excellent conductivity and stable signal performance.



SECURE CONNECTION

Precision-engineered interface ensures a firm and dependable fit.



DURABLE CONSTRUCTION

Nickel plated metal body offers strength, corrosion resistance and long service life.



EASY INSTALLATION

Compact connector design allows quick and convenient usage.



WIDE APPLICATION

Suitable for RF systems, CATV, communication equipment and test setups.

SPECIFICATIONS

Product Name	RF Female / F Female Connector (Pin G.P.)
Connector Type	RF Female to F Female
Contact Material	Brass (Gold Plated Pin)
Body Material	Brass (Nickel Plated)
Insulator Material	PTFE / Teflon
Impedance	75 Ω
Frequency Range	DC – 3 GHz
Voltage Rating	250 V RMS
Contact Resistance	≤ 20 m Ω
Insulation Resistance	≥ 1000 M Ω
Operating Temperature	-20°C to +70°C
Application	RF, CATV, Communication, Test Equipment
RoHS Compliant	Yes

APPLICATIONS



RF Systems



CATV Networks



Communication Equipment



Test & Measurement



Broadcast Systems



Industrial Applications



QUALITY ASSURED



BUILT FOR PRECISION



RELIABLE & SAFE



CUSTOMER SUPPORT



pradecp@rfconnector.in

9810138894

www.synergyppl.com

F QUICK / F FEMALE CONNECTOR (PIN G.P.)



High quality F Quick / F Female Connector with gold plated pin contact for reliable signal transmission and secure connectivity. Built with durable metal construction for low loss, corrosion resistance, and long service life. Ideal for RF, CATV, communication, and test applications.



GOLD PLATED PIN

Gold plated pin provides excellent conductivity and stable signal performance.



SECURE CONNECTION

Precision-engineered interface ensures a firm and dependable fit.



DURABLE CONSTRUCTION

Nickel plated metal body offers strength, corrosion resistance and long service life.



EASY INSTALLATION

Compact connector design allows quick and convenient usage.



WIDE APPLICATION

Suitable for RF systems, CATV networks, communication equipment and test setups.

SPECIFICATIONS

Product Name	F Quick / F Female Connector (Pin G.P.)
Connector Type	F Quick to F Female
Contact Material	Brass (Gold Plated Pin)
Body Material	Brass (Nickel Plated)
Insulator Material	PTFE / Teflon
Impedance	75 Ω
Frequency Range	DC - 3 GHz
Voltage Rating	250 V RMS
Contact Resistance	≤ 20 m Ω
Insulation Resistance	≥ 1000 M Ω
Operating Temperature	-20°C to +70°C
Application	RF, CATV, Communication, Test Equipment
RoHS Compliant	Yes

APPLICATIONS



RF Systems



CATV Networks



Communication Equipment



Test & Measurement



Broadcast Systems



Industrial Applications



QUALITY ASSURED



BUILT FOR PRECISION



RELIABLE & SAFE



CUSTOMER SUPPORT



✉ pradeep@rfconnector.in

☎ 9810138894



www.synergypnl.com

F MALE / F MALE CONNECTOR (PIN G.P.)



RoHS COMPLIANT

High quality F Male / F Male Connector with Gold Plated Pins (G.P.) ensures excellent signal transmission and low loss performance. Durable and corrosion resistant design suitable for CATV, Satellite, Broadband and other RF applications.



PREMIUM QUALITY

High grade materials ensure excellent performance and reliability.



SECURE CONNECTION

Precision engineered threads ensure a tight and stable connection.



DURABLE CONSTRUCTION

Nickel plated body for enhanced corrosion resistance and durability.



LOW SIGNAL LOSS

Designed to deliver optimum signal transmission with minimal loss.



WIDE APPLICATION

Ideal for CATV, Satellite, Broadband, Cable TV and RF applications.

SPECIFICATIONS

Product Name	F Male / F Male Connector (Pin G.P.)
Connector Type	F Male to F Male
Connector Interface	F Type (Threaded)
Pin Material	Brass (Gold Plated)
Body Material	Brass (Nickel Plated)
Insulator Material	PTFE
Connection Type	Threaded
Impedance	75 Ohm
Frequency Range	5 MHz – 3 GHz
VSWR	≤ 1.3
Insertion Loss	≤ 0.2 dB
Operating Temperature	-20°C to +85°C
Application	CATV, Satellite, Broadband, Cable TV, RF Applications
RoHS Compliant	Yes

APPLICATIONS



Satellite Systems



CATV Systems



Broadband Networks



Cable TV Applications



RF Applications



Home Entertainment



QUALITY ASSURED

Tested for high performance and reliability



BUILT FOR PRECISION

Accurate connections for critical applications



RELIABLE & SAFE

Designed for repeated and safe use



CUSTOMER SUPPORT

Dedicated support for all your technical needs




✉ pradeep@rfconnector.in

☎ 9810138894

🌐 www.synergypnl.com

SCART MALE 21 PIN / 3 RCA FEMALE + S-VHS CONNECTOR

RoHS
COMPLIANT



High quality SCART Male 21 Pin to 3 RCA Female + S-VHS Connector adapter for audio and video signal conversion. Provides stable connection and excellent performance for home theater, multimedia systems and professional applications.



PREMIUM QUALITY

High grade materials ensure durability and long life.



AUDIO & VIDEO OUTPUT

3 RCA female (Yellow/Video, White/Audio L, Red/Audio R) + S-VHS output.



SECURE CONNECTION

SCART 21 pin male connector ensures stable and reliable signal transmission.



PLUG & PLAY

Easy to install and use. No additional driver or software required.



WIDE COMPATIBILITY

Ideal for TV, DVD, VCR, Set-top Box, Projectors, and AV Receivers.

SPECIFICATIONS

Product Name	SCART Male 21 Pin to 3 RCA Female + S-VHS Connector
Input Connector	SCART Male 21 Pin
Output Connectors	3 RCA Female (Yellow, White, Red) + S-VHS Female
RCA Function	Yellow – Video White – Audio Left Red – Audio Right
S-VHS Function	S-VHS – Video (Y/C)
Connector Material	Nickel Plated
Body Material	ABS
Color	Black
Application	TV, DVD, VCR, Set-top Box, Projectors, Home Theater Systems
Packaging	Poly Bag
RoHS Compliant	Yes

APPLICATIONS



Television



DVD Players



Set-top Boxes



VCR Systems



Projectors



Home Theater Systems



QUALITY ASSURED

Tested for high performance and reliability



BUILT FOR PRECISION

Accurate connections for critical applications



RELIABLE & SAFE

Designed for repeated and safe use



CUSTOMER SUPPORT

Dedicated support for all your technical needs



✉ pradeep@rfconnector.in ☎ 9810138894

🌐 www.synergypnl.com

SCART MALE 21 PIN / 2 RCA FEMALE CONNECTOR W / SWITCH



High quality SCART Male 21 Pin to 2 RCA Female Connector with Switch for audio and video signal conversion. Switch allows easy selection between TV and OUT modes. Provides stable connection and excellent performance for home theater and multimedia applications.



PREMIUM QUALITY

High grade materials ensure durability and long life.



AUDIO & VIDEO OUTPUT

2 RCA female (Yellow - Video, White - Audio L) output.



BUILT-IN SWITCH

Switch for easy selection between TV and OUT modes.



PLUG & PLAY

Easy to install and use. No additional driver or software required.



WIDE COMPATIBILITY

Ideal for TV, DVD, Set-top Box, VCR, Projectors and other AV devices.



SPECIFICATIONS

Product Name	SCART Male 21 Pin to 2 RCA Female Connector w / Switch
Input Connector	SCART Male 21 Pin
Output Connectors	2 RCA Female (Yellow - Video, White - Audio L)
Switch Function	TV / OUT Switch
SCART Standard	21 Pin
Connector Material	Nickel Plated
Body Material	ABS
Color	Black
Application	TV, DVD, VCR, Set-top Box, Projectors, Home Theater Systems
Packaging	Poly Bag
RoHS Compliant	Yes

APPLICATIONS



Television



DVD Players



Set-top Boxes



Projectors



VCR Systems



Home Theater Systems



QUALITY ASSURED

Tested for high performance and reliability



BUILT FOR PRECISION

Accurate connections for critical applications.



RELIABLE & SAFE

Designed for repeated and safe use



CUSTOMER SUPPORT

Dedicated support for all your technical needs



pradecp@rfconnector.in

9810138894

www.synergyppl.com

VCR / 2 TV-2 MA / 1FE CONNECTOR

VCR / 2 TV-2 MA / 1FE connector is designed for efficient signal splitting and connection in television, VCR, RF, and home entertainment applications. It delivers reliable connectivity and stable performance with durable construction for long-lasting use.



RELIABLE CONNECTIVITY

Ensures stable signal transmission with minimal loss and interference.



DURABLE CONSTRUCTION

High-quality materials provide long-lasting performance and corrosion resistance.



EASY INSTALLATION

Plug-and-play design for quick and hassle-free setup.



SIGNAL DISTRIBUTION

Efficiently splits and distributes signals to multiple outputs.



WIDE COMPATIBILITY

Compatible with TV, VCR, RF systems and various audio/video devices.

SPECIFICATIONS

Product Name	VCR / 2 TV-2 MA / 1FE Connector
Connector Type	RF Signal Splitter / Adapter
Input / Output	1 Input (F Female) to 2 Outputs (2 x TV Male + 1 x F Female)
Body Material	Metal with ABS Label
Contact Material	Nickel Plated Brass
Finish	Nickel Plated
Impedance	75 Ohm
Frequency Range	5 MHz – 1000 MHz
Connector Ends	1 x F Female (Input) 2 x TV Male + 1 x F Female (Output)
Operating Temperature	-20°C to +60°C
Application	Television, VCR, RF, Home Entertainment Systems
RoHS Compliant	Yes

APPLICATIONS



Television



VCR Systems



RF Systems



Home Entertainment



Audio/Video Equipment



Consumer Electronics



QUALITY ASSURED



BUILT FOR PRECISION



RELIABLE & SAFE



CUSTOMER SUPPORT



pradecp@rfconnector.in

9810138894

www.synergyppl.com

VCR / 2 TV-2 FE / 1MA CONNECTOR

VCR / 2 TV-2 FE / 1MA Connector is designed for signal splitting and connection in television, VCR, RF, and home entertainment applications. It ensures reliable connectivity, low signal loss, and stable performance for clear and interference-free transmission.



RELIABLE CONNECTIVITY

Ensures secure and stable connections for uninterrupted signal transmission.



DURABLE CONSTRUCTION

Robust build quality for long-lasting performance and reliability.



EASY INSTALLATION

Simple plug-and-play design for quick and hassle-free setup.



SIGNAL DISTRIBUTION

Efficiently splits signal to multiple outputs with minimal loss.



WIDE COMPATIBILITY

Compatible with VCR, TV, RF and home entertainment devices.

SPECIFICATIONS

Product Name	VCR / 2 TV-2 FE / 1MA Connector
Connector Type	2-Way Signal Splitter
Input / Output	1 Input (VCR) to 2 Outputs (TV-2, FE/1MA)
Body Material	Zinc Alloy / ABS
Contact Material	Brass
Finish	Nickel Plated
Impedance	75 Ω
Frequency Range	5 MHz – 862 MHz
Connector Ends	IEC Male (1) to IEC Female (2)
Operating Temperature	-20°C to +60°C
Application	VCR, TV, RF, Home Entertainment
RoHS Compliant	Yes

APPLICATIONS



Television



VCR Systems



RF Systems



Home Entertainment



Audio/Video Equipment



Consumer Electronics



QUALITY ASSURED



BUILT FOR PRECISION



RELIABLE & SAFE



CUSTOMER SUPPORT



pradecp@rfconnector.in

9810138894

www.synergyppl.com

SCART MALE 21 PIN / 3 RCA FEMALE + S-VHS CONNECTOR W / SWITCH

High quality SCART Male 21 Pin to 3 RCA Female + S-VHS Connector with switch, designed for reliable audio and video signal conversion. The switch allows easy selection between input and output modes, making it ideal for TV, DVD, VCR, set-top boxes, projectors, and home theater applications. Built for stable connectivity and convenient plug-and-play use.



PREMIUM QUALITY

Durable construction ensures long service life and dependable performance.



AUDIO & VIDEO OUTPUT

Provides 3 RCA female outputs for AV connectivity plus S-VHS support.



BUILT-IN SWITCH

Easy input/output mode selection with the integrated switch.



PLUG & PLAY

Quick installation with no additional software or drivers required.



WIDE COMPATIBILITY

Suitable for televisions, DVD players, VCR systems, projectors, and home theater devices.



SPECIFICATIONS

Product Name	SCART Male 21 Pin / 3 RCA Female + S-VHS Connector w / Switch
Input Connector	SCART Male 21 Pin
Output Connectors	3 RCA Female + S-VHS Female
Switch Function	IN / OUT Switch
RCA Functions	Yellow: Video, White: Audio Left, Red: Audio Right
Body Material	ABS
Contact Material	Nickel Plated
Color	Black
Application	TV, DVD, VCR, Set-top Box, Projectors, Home Theater Systems
Packaging	Poly Bag
RoHS Compliant	Yes

APPLICATIONS



Television



DVD Players



Set-top Boxes



VCR Systems



Projectors



Home Theater Systems



QUALITY ASSURED



BUILT FOR PRECISION



RELIABLE & SAFE



CUSTOMER SUPPORT



pradecp@rfconnector.in

9810138894

www.synergypL.com

L.S. MALE / RCA FEMALE CONNECTOR

High quality L.S. Male to RCA Female Connector designed for reliable audio and signal connectivity. Compact construction ensures secure fitting, low signal loss, and long service life. Ideal for consumer electronics, audio equipment, and general connection applications.



SECURE CONNECTION

Provides stable and dependable connectivity for everyday use.



DURABLE CONSTRUCTION

Strong body design offers long-lasting performance.



LOW SIGNAL LOSS

Designed for clear signal transfer with minimal interference.



COMPACT DESIGN

Small and practical connector for convenient installation.



WIDE APPLICATION

Suitable for audio systems, consumer electronics, and accessories.

SPECIFICATIONS

Product Name	L.S. Male / RCA Female Connector
Connector Type	L.S. Male to RCA Female
Interface	2 Pin Male to RCA Female
Contact Material	Brass
Body Material	PVC / Metal
Insulator Material	PVC
Impedance	75 Ω
Frequency Range	DC – 1 GHz
Voltage Rating	50 V
Contact Resistance	≤ 20 m Ω
Insulation Resistance	≥ 1000 M Ω
Operating Temperature	-20°C to +70°C
Application	Audio, Consumer Electronics, General Connectivity
RoHS Compliant	Yes

APPLICATIONS



Audio Systems



Consumer Electronics



TV Equipment



Accessories



Communication Devices



General Use



QUALITY ASSURED



BUILT FOR PRECISION



RELIABLE & SAFE



CUSTOMER SUPPORT



✉ pradeep@rfconnector.in



9810138894



www.synergytpl.com

EP JACK 3.5 mm / 5 PIN FEMALE CONNECTOR



High quality EP Jack 3.5 mm / 5 Pin Female Connector ensures reliable audio connectivity for stereo and microphone signals. Durable construction with precise engineering provides excellent performance and long life.



PREMIUM QUALITY

High grade materials ensure durability and long life.



CLEAR AUDIO OUTPUT

5 Pin configuration for stereo audio + microphone support.



SECURE CONNECTION

Tight fit and stable connection for uninterrupted performance.



EASY TO INSTALL

Plug and play design for quick and hassle-free installation.



WIDE COMPATIBILITY

Compatible with various audio devices, headsets, speakers and microphones.

SPECIFICATIONS

Product Name	EP Jack 3.5 mm / 5 Pin Female Connector
Connector Type	3.5 mm Female Jack
Pin Configuration	5 Pin (TRRS)
Connector Material	Nickel Plated
Body Material	ABS
Contact Material	Brass
Insulator Material	Plastic
Audio Support	Stereo Audio + Microphone
Frequency Response	20 Hz – 20 KHz
Impedance	32 Ohm
Voltage Rating	30V DC
Application	Headsets, Microphones, Speakers, Audio Systems, Communication Devices
RoHS Compliant	Yes

APPLICATIONS



Headsets



Microphones



Speakers



Laptops & PCs



Mobile Devices



Audio Systems



QUALITY ASSURED

Tested for high performance and reliability



BUILT FOR PRECISION

Accurate connections for critical applications



RELIABLE & SAFE

Designed for repeated and safe use



CUSTOMER SUPPORT

Dedicated support for all your technical needs



pradecp@rfconnector.in

9810138894

www.synergypnl.com

EP ST JACK 3.5 mm / 5 PIN MALE CONNECTOR

EP ST Jack 3.5 mm / 5 Pin Male Connector is engineered for reliable audio connectivity. It features a 3.5 mm stereo plug with five conductors, ensuring stable performance and secure fitting. Built with high-quality materials, it offers durability, corrosion resistance and long-lasting operation. Ideal for professional audio equipment, consumer electronics and general electronic applications.



PREMIUM QUALITY

Made from high-quality materials for reliable and consistent use.



SECURE CONNECTION

Precision design ensures a firm and stable connection every time.



DURABLE CONSTRUCTION

Robust build for long-lasting performance and daily use.



CLEAR SIGNAL TRANSFER

Ensures minimal signal loss for high-quality audio performance.



WIDE COMPATIBILITY

Works with a wide range of audio and electronic devices.

SPECIFICATIONS

Product Name	EP ST Jack 3.5 mm / 5 Pin Male Connector
Connector Type	EP ST Jack
Interface	3.5 mm Stereo Plug
Pin Configuration	5 Pin (TRRS + Mic)
Contact Material	Nickel Plated Brass
Body Material	PVC
Insulator Material	PBT
Impedance	32 Ω
Frequency Range	20 Hz to 20 kHz
Voltage Rating	30 V DC
Contact Resistance	≤ 30 m Ω
Insulation Resistance	≥ 100 M Ω
Operating Temperature	-20 $^{\circ}$ C to +70 $^{\circ}$ C
Application	Audio & Electronic Equipment
RoHS Compliant	Yes

APPLICATIONS



Audio Systems



Consumer Electronics



Mobile Devices



Communication Devices



Accessories



General Use



QUALITY ASSURED



BUILT FOR PRECISION



RELIABLE & SAFE



CUSTOMER SUPPORT



✉ pradeep@rfconnector.in



9810138894



www.synergyppl.com

RCA MALE CONNECTOR F.M. W/SPRING G.P.



High quality RCA Male Connector F.M. with Spring Gold Plated (G.P.) ensures excellent signal transmission and superior audio performance. Durable construction with spring strain relief for secure connection and long life.



PREMIUM QUALITY

Gold plated contacts for excellent conductivity and corrosion resistance.



SUPERIOR SIGNAL

Ensures low signal loss and high fidelity audio performance.



SPRING STRAIN RELIEF

Spring G.P. design provides flexibility and prevents cable damage.



SECURE CONNECTION

Firm grip and reliable connection for uninterrupted audio transmission.



WIDE APPLICATION

Ideal for audio systems, amplifiers, speakers, home theaters and more.

SPECIFICATIONS

Product Name	RCA Male Connector F.M. w/ Spring G.P.
Connector Type	RCA Male (F.M.)
Plating	Gold Plated (G.P.)
Body Material	Brass
Spring	Spring Gold Plated
Insulator Material	Plastic
Contact Material	Brass
Connection Type	Solder Type
Application	Audio Systems, Amplifiers, Speakers, Home Theater, Car Audio
Color Options	● ● ●
RoHS Compliant	Yes

APPLICATIONS



Audio Systems



Amplifiers



Speakers



Home Theaters



Car Audio



Mixers



Headphones



QUALITY ASSURED

Tested for high performance and reliability



BUILT FOR PRECISION

Accurate connections for critical applications



RELIABLE & SAFE

Designed for repeated and safe use



CUSTOMER SUPPORT

Dedicated support for all your technical needs



✉ pradeep@rfconnector.in



9810138894



www.synergypnl.com

RCA MALE / EP FEMALE 3.5 mm CONNECTOR



High quality RCA Male to EP Female 3.5 mm Connector ensures stable audio signal transmission with excellent performance. Durable design for reliable connection in audio and video applications.



PREMIUM QUALITY

High grade materials ensure durability and long life.



STABLE AUDIO SIGNAL

Ensures clear and reliable audio signal transmission with minimal loss.



SECURE CONNECTION

Firm grip and precise design provides stable and secure connection.



EASY TO INSTALL

Simple plug-and-play installation, no additional tools required.



WIDE COMPATIBILITY

Ideal for audio systems, speakers, amplifiers, home theaters and more.

SPECIFICATIONS

Product Name	RCA Male / EP Female 3.5 mm Connector
Connector Type	RCA Male to EP 3.5 mm Female
RCA Connector	RCA Male (Center Pin)
EP Connector	3.5 mm EP Female
Body Material	ABS
Connector Material	Nickel Plated
Contact Material	Brass
Insulator Material	Plastic
Audio Signal Type	Stereo / Mono
Application	Audio & Video Equipment, Home Theater, Amplifiers, Speakers, AV Systems
Packaging	Poly Bag
RoHS Compliant	Yes

APPLICATIONS



Audio Systems



Amplifiers



Speakers



Home Theaters



TV & AV Equipment



Mixers



QUALITY ASSURED

Tested for high performance and reliability



BUILT FOR PRECISION

Accurate connections for critical applications



RELIABLE & SAFE

Designed for repeated and safe use



CUSTOMER SUPPORT

Dedicated support for all your technical needs



✉ pradeep@rfconnector.in

☎ 9810138894

🌐 www.synergyppl.com

TV / VCR CORD DLX 1.5 MTR

RoHS
COMPLIANT



High quality TV / VCR Cord DLX 1.5 MTR with premium connectors for clear and stable signal transmission. Ideal for connecting TV, VCR, Set-top Box and other audio/video devices. Durable cable with excellent performance and long life.



PREMIUM QUALITY

High grade materials ensure durability and long life.



CLEAR SIGNAL

Ensures clear and stable audio & video signal transmission.



SECURE CONNECTION

Precision connectors for tight and reliable connection.



DURABLE CABLE

Strong and flexible cable with strain relief for long-lasting performance.



WIDE COMPATIBILITY

Compatible with TVs, VCRs, Set-top Boxes, DVD Players and other AV devices.

SPECIFICATIONS

Product Name	TV / VCR Cord DLX 1.5 MTR
Cable Length	1.5 Meter
Connector Type	TV Male to TV Female (IEC 9.5 mm)
Connector Material	Nickel Plated
Cable Type	Coaxial
Impedance	75 Ohm
Jacket Material	PVC
Color	Black
Application	TV, VCR, Set-top Box, DVD Player, DTH Receiver, Home Entertainment Systems
Packaging	Poly Bag
RoHS Compliant	Yes

APPLICATIONS



Television



VCR Players



Set-top Boxes



DVD Players



DTH Receivers



Home Entertainment



QUALITY ASSURED

Tested for high performance and reliability



BUILT FOR PRECISION

Accurate connections for critical applications



RELIABLE & SAFE

Designed for repeated and safe use



CUSTOMER SUPPORT

Dedicated support for all your technical needs



pradecp@rfconnector.in

9810138894

www.synergyppl.com

TV / VCR CORD DUAL MOULDED 1.5 MTR

High quality TV / VCR Cord Dual Moulded 1.5 MTR designed for reliable audio-video signal transmission. The dual moulded construction offers better grip, strain relief, and long service life. Ideal for connecting TV, VCR, set-top box, and home entertainment equipment.



DUAL MOULDED DESIGN

Strong moulded ends provide durability and cable protection.



CLEAR SIGNAL

Supports stable audio and video signal transmission.



SECURE CONNECTION

Reliable connector fit for uninterrupted performance.



DURABLE CABLE

Flexible PVC cable jacket for long service life.



WIDE COMPATIBILITY

Suitable for TVs, VCRs, set-top boxes, and AV devices.

SPECIFICATIONS

Product Name	TV / VCR Cord Dual Moulded 1.5 MTR
Cable Length	1.5 Meter
Connector Type	TV / VCR Cord
End Construction	Dual Moulded
Cable Type	Coaxial Cable
Connector Material	Nickel Plated
Jacket Material	PVC
Color	Black Cable with Yellow Moulded Ends
Impedance	75 Ohm
Signal Type	Audio / Video
Application	TV, VCR, Set-top Box, AV Equipment
RoHS Compliant	Yes

APPLICATIONS



Television



VCR Players



Set-top Boxes



DVD Players



DTH Receivers



Home Entertainment



QUALITY
ASSURED



BUILT FOR
PRECISION



RELIABLE
& SAFE



CUSTOMER
SUPPORT



pradecp@rfconnector.in

9810138894

www.synergyppl.com

TV / VCR CORD F.M.1.5 MTR

High quality TV / VCR Cord F.M.1.5 MTR with reliable female-to-male connectors for clear and stable signal transmission. Ideal for connecting TV, VCR, set-top box and other audio/video devices. Durable cable construction ensures dependable performance and long service life.



PREMIUM QUALITY

High grade materials ensure durability and long life.



CLEAR SIGNAL

Ensures clear and stable audio & video signal transmission.



SECURE CONNECTION

Precision connectors provide tight and reliable connection.



DURABLE CABLE

Flexible and strong cable with strain relief for long-lasting performance.



WIDE COMPATIBILITY

Compatible with TVs, VCRs, set-top boxes, DVD players and other AV devices.

SPECIFICATIONS

Product Name	TV / VCR Cord F.M.1.5 MTR
Cable Length	1.5 Meter
Connector Type	TV Female to TV Male (IEC 9.5 mm)
Connector Material	Nickel Plated
Cable Type	Coaxial
Jacket Material	PVC
Color	Black Cable with Blue Sleeve
Impedance	75 Ohm
Signal Type	Audio / Video
Application	TV, VCR, Set-top Box, DVD Player, DTH Receiver, Home Entertainment Systems
Packaging	Poly Bag
RoHS Compliant	Yes

APPLICATIONS



Television



VCR Players



Set-top Boxes



DVD Players



DTH Receivers



Home Entertainment



QUALITY
ASSURED



BUILT FOR
PRECISION



RELIABLE
& SAFE



CUSTOMER
SUPPORT



pradecp@rfconnector.in

9810138894

www.synergyppl.com

BNC MALE / BNC MALE CORD DUAL MOULDED 1.5 MTR

High quality BNC Male / BNC Male Cord Dual Moulded 1.5 MTR designed for reliable video, RF, CCTV and communication signal transmission. The dual moulded ends provide excellent grip, improved strain relief and dependable performance for daily use. Ideal for secure connections in test, broadcast and surveillance applications.



DUAL MOULDED DESIGN

Strong moulded ends provide durability and cable protection.



SECURE BNC FIT

Precision BNC male connectors ensure stable and tight locking connection.



CLEAR SIGNAL

Supports reliable RF and video signal transmission with low loss.



DURABLE CABLE

Flexible cable construction offers long service life and dependable use.



WIDE APPLICATION

Suitable for CCTV systems, RF equipment, test benches and broadcasting setups.

SPECIFICATIONS

Product Name	BNC Male / BNC Male Cord Dual Moulded 1.5 MTR
Cable Length	1.5 Meter
Connector Type	BNC Male to BNC Male
End Construction	Dual Moulded
Connector Material	Nickel Plated Brass
Cable Type	Coaxial Cable
Jacket Material	PVC
Color	Black Cable with Yellow Moulded Ends
Impedance	75 Ohm
Signal Type	RF / Video
Application	CCTV Systems, RF Equipment, Test & Measurement, Broadcasting
RoHS Compliant	Yes

APPLICATIONS



CCTV Systems



RF Systems



Test & Measurement



Broadcasting



Communication Equipment



Video Systems



QUALITY ASSURED



BUILT FOR PRECISION



RELIABLE & SAFE



CUSTOMER SUPPORT



pradecp@rfconnector.in

9810138894

www.synergyppl.com

BNC MALE / BNC MALE CORD DUAL MOULDED 1.5 MTR

High quality BNC Male / BNC Male Cord Dual Moulded 1.5 MTR designed for reliable video, RF, CCTV and communication signal transmission. The dual moulded ends provide excellent grip, improved strain relief and dependable performance for daily use. Ideal for secure connections in test, broadcast and surveillance applications.



QTY : 20



DUAL MOULDED DESIGN

Strong moulded ends provide durability and cable protection.



SECURE BNC FIT

Precision BNC male connectors ensure stable and tight locking connection.



CLEAR SIGNAL

Supports reliable RF and video signal transmission with low loss.



DURABLE CABLE

Flexible cable construction offers long service life and dependable use.



WIDE APPLICATION

Suitable for CCTV systems, RF equipment, test benches and broadcasting setups.

SPECIFICATIONS

Product Name	BNC Male / BNC Male Cord Dual Moulded 1.5 MTR
Cable Length	1.5 Meter
Connector Type	BNC Male to BNC Male
End Construction	Dual Moulded
Connector Material	Nickel Plated Brass
Cable Type	Coaxial Cable
Jacket Material	PVC
Color	Black Cable with Yellow Moulded Ends
Impedance	75 Ohm
Signal Type	RF / Video
Application	CCTV Systems, RF Equipment, Test & Measurement, Broadcasting
RoHS Compliant	Yes

APPLICATIONS



CCTV Systems



RF Systems



Test & Measurement



Broadcasting



Communication Equipment



Video Systems



QUALITY ASSURED



BUILT FOR PRECISION



RELIABLE & SAFE



CUSTOMER SUPPORT