


DC TO 26.5 GHZ 2.92mm* ATTENUATORS

IMSTDANCE: 50 Ohms
 ACCURACY: 1 THRU 6 dB, $\pm .5$ dB
 10 AND 20 dB, $\pm .6$ dB
 30 dB, $\pm .8$ dB
 VSWR: 1.40:1 MAXIMUM




AVERAGE POWER HANDLING CAPABILITY: 2 WATTS

Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7024-1	1 dB	\$177.60	\$165.17	\$152.74	\$142.08
ST7024-2	2 dB	177.60	165.17	152.74	142.08
ST7024-3	3 dB	177.60	165.17	152.74	142.08
ST7024-6	6 dB	177.60	165.17	152.74	142.08
ST7024-10	10 dB	177.60	165.17	152.74	142.08
ST7024-20	20 dB	177.60	165.17	152.74	142.08
ST7024-30	30 dB	177.60	165.17	152.74	142.08

*2.92mm CONNECTORS WILL MATE BOTH ELECTRICALLY AND MECHANICALLY WITH ALL SMA, 3.5mm & K CONNECTORS. THE K CONNECTOR IS A REGISTERED TRADEMARK OF THE ANRITSU COMPANY.

DC TO 40 GHZ 2.92mm* ATTENUATORS

IMSTDANCE: 50 Ohms
 ACCURACY: 3 AND 6 dB, $\pm .8$ dB
 10 THRU 30 dB, ± 1.0 dB



VSWR: 1.40:1 MAXIMUM


AVERAGE POWER HANDLING CAPABILITY: .5 WATT

Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7046-3	3 dB	\$313.45	\$291.51	\$269.57	\$250.76
ST7046-6	6 dB	313.45	291.51	269.57	250.76
ST7046-10	10 dB	313.45	291.51	269.57	250.76
ST7046-20	20 dB	313.45	291.51	269.57	250.76
ST7046-30	30 dB	313.45	291.51	269.57	250.76

*2.92mm CONNECTORS WILL MATE BOTH ELECTRICALLY AND MECHANICALLY WITH ALL SMA, 3.5mm & K CONNECTORS. THE K CONNECTOR IS A REGISTERED TRADEMARK OF THE ANRITSU COMPANY.

DC TO 18 GHZ 7mm ATTENUATORS

IMSTDANCE: 50 Ohms
 ACCURACY: 1 THRU 6 dB, $\pm .3$ dB
 10 AND 20 dB, $\pm .5$ dB
 30 dB, $\pm .75$ dB
 VSWR: 1.20:1 MAXIMUM




AVERAGE POWER HANDLING CAPABILITY: 2 WATTS

Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7023-1	1 dB	\$365.70	\$340.10	\$314.50	\$292.56
ST7023-2	2 dB	365.70	340.10	314.50	292.56
ST7023-3	3 dB	365.70	340.10	314.50	292.56
ST7023-6	6 dB	365.70	340.10	314.50	292.56
ST7023-10	10 dB	365.70	340.10	314.50	292.56
ST7023-20	20 dB	365.70	340.10	314.50	292.56
ST7023-30	30 dB	365.70	340.10	314.50	292.56

1 WATT, DC TO 2 GHZ SMA ATTENUATORS

ACCURACY: 1 THRU 10 dB, $\pm .6$ dB
 12, 15, & 20 dB, $\pm .75$ dB
 30 dB $\pm .90$ dB, 40 dB ± 1.50 dB




VSWR: 1.2:1 MAXIMUM

Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7161-1	1 dB	\$39.95	\$37.15	\$34.36	\$31.96
ST7161-2	2 dB	39.95	37.15	34.36	31.96
ST7161-3	3 dB	39.95	37.15	34.36	31.96
ST7161-4	4 dB	39.95	37.15	34.36	31.96
ST7161-5	5 dB	39.95	37.15	34.36	31.96
ST7161-6	6 dB	39.95	37.15	34.36	31.96
ST7161-7	7 dB	39.95	37.15	34.36	31.96
ST7161-8	8 dB	39.95	37.15	34.36	31.96
ST7161-9	9 dB	39.95	37.15	34.36	31.96
ST7161-10	10 dB	39.95	37.15	34.36	31.96
ST7161-12	12 dB	39.95	37.15	34.36	31.96
ST7161-15	15 dB	39.95	37.15	34.36	31.96
ST7161-20	20 dB	39.95	37.15	34.36	31.96
ST7161-30	30 dB	39.95	37.15	34.36	31.96
ST7161-40	40 dB	39.95	37.15	34.36	31.96

2 WATT, DC TO 3 GHZ SMA ATTENUATORS


ACCURACY: 1 THRU 10 dB, $\pm .5$ dB
 12, 15 & 20 dB, $\pm .75$ dB
 30 & 40 dB, ± 1.50 dB
 VSWR: 1.15:1 MAXIMUM



Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7001-1	1 dB	\$52.20	\$48.55	\$44.89	\$41.76
ST7001-2	2 dB	52.20	48.55	44.89	41.76
ST7001-3	3 dB	52.20	48.55	44.89	41.76
ST7001-4	4 dB	52.20	48.55	44.89	41.76
ST7001-5	5 dB	52.20	48.55	44.89	41.76
ST7001-6	6 dB	52.20	48.55	44.89	41.76
ST7001-7	7 dB	52.20	48.55	44.89	41.76
ST7001-8	8 dB	52.20	48.55	44.89	41.76
ST7001-9	9 dB	52.20	48.55	44.89	41.76
ST7001-10	10 dB	52.20	48.55	44.89	41.76
ST7001-12	12 dB	52.20	48.55	44.89	41.76
ST7001-15	15 dB	52.20	48.55	44.89	41.76
ST7001-20	20 dB	52.20	48.55	44.89	41.76
ST7001-30	30 dB	52.20	48.55	44.89	41.76
ST7001-40	40 dB	67.85	63.10	58.35	54.28

2 WATTS, DC TO 6 GHZ SMA ATTENUATORS

ACCURACY: 1 THRU 10 dB, $\pm .6$ dB
 12, 15, & 20 dB, $\pm .75$ dB
 30 dB $\pm .90$ dB, 40 dB ± 1.50 dB




VSWR: 1.2:1 MAXIMUM

Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7162-1	1 dB	\$59.95	\$55.75	\$51.56	\$47.96
ST7162-2	2 dB	59.95	55.75	51.56	47.96
ST7162-3	3 dB	59.95	55.75	51.56	47.96
ST7162-4	4 dB	59.95	55.75	51.56	47.96
ST7162-5	5 dB	59.95	55.75	51.56	47.96
ST7162-6	6 dB	59.95	55.75	51.56	47.96
ST7162-7	7 dB	59.95	55.75	51.56	47.96
ST7162-8	8 dB	59.95	55.75	51.56	47.96
ST7162-9	9 dB	59.95	55.75	51.56	47.96
ST7162-10	10 dB	59.95	55.75	51.56	47.96
ST7162-12	12 dB	59.95	55.75	51.56	47.96
ST7162-15	15 dB	59.95	55.75	51.56	47.96
ST7162-20	20 dB	59.95	55.75	51.56	47.96
ST7162-30	30 dB	59.95	55.75	51.56	47.96
ST7162-40	40 dB	59.95	55.75	51.56	47.96

2 WATTS, DC TO 12.4 GHZ SMA ATTENUATORS


ACCURACY: 1 THRU 10 dB, $\pm .5$ dB
 12, 15 & 20 dB, $\pm .75$ dB
 30 & 40 dB, ± 1.50 dB
 VSWR: 1.25:1 MAXIMUM



Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7045-1	1 dB	\$73.10	\$67.98	\$62.87	\$58.48
ST7045-2	2 dB	73.10	67.98	62.87	58.48
ST7045-3	3 dB	73.10	67.98	62.87	58.48
ST7045-4	4 dB	73.10	67.98	62.87	58.48
ST7045-5	5 dB	73.10	67.98	62.87	58.48
ST7045-6	6 dB	73.10	67.98	62.87	58.48
ST7045-7	7 dB	73.10	67.98	62.87	58.48
ST7045-8	8 dB	73.10	67.98	62.87	58.48
ST7045-9	9 dB	73.10	67.98	62.87	58.48
ST7045-10	10 dB	73.10	67.98	62.87	58.48
ST7045-12	12 dB	73.10	67.98	62.87	58.48
ST7045-15	15 dB	73.10	67.98	62.87	58.48
ST7045-20	20 dB	73.10	67.98	62.87	58.48
ST7045-30	30 dB	73.10	67.98	62.87	58.48
ST7045-40	40 dB	94.00	87.42	80.84	75.20

2 WATTS, DC TO 18 GHZ SMA ATTENUATORS

ACCURACY: 1 THRU 10 dB, $\pm .5$ dB
 12, 15 & 20 dB, $\pm .75$ dB
 30 & 40 dB, ± 1.50 dB



VSWR: 1.35:1 MAX

Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7005-1	1 dB	\$85.20	\$79.24	\$73.27	\$68.16
ST7005-2	2 dB	83.55	77.70	71.85	66.84
ST7005-3	3 dB	85.20	79.24	73.27	68.16
ST7005-4	4 dB	83.55	77.70	71.85	66.84
ST7005-5	5 dB	83.55	77.70	71.85	66.84
ST7005-6	6 dB	85.20	79.24	73.27	68.16
ST7005-7	7 dB	83.55	77.70	71.85	66.84
ST7005-8	8 dB	83.55	77.70	71.85	66.84
ST7005-9	9 dB	83.55	77.70	71.85	66.84
ST7005-10	10 dB	85.20	79.24	73.27	68.16
ST7005-12	12 dB	83.55	77.70	71.85	66.84
ST7005-15	15 dB	83.55	77.70	71.85	66.84
ST7005-20	20 dB	85.20	79.24	73.27	68.16
ST7005-30	30 dB	85.20	79.24	73.27	68.16
ST7005-40	40 dB	106.55	99.09	91.63	85.24