


5 WATT, DC TO 18 GHZ TNC ATTENUATORS


IMSTDANCE: 50 Ohms
 ACCURACY: 1 THRU 6 dB, $\pm .3$ dB
 10 AND 20 dB, $\pm .5$ dB
 30 dB, ± 1.5 dB
 VSWR: 1.35:1 MAXIMUM



Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7052-1	1 dB	\$208.95	\$194.32	\$179.70	\$167.16
ST7052-2	2 dB	208.95	194.32	179.70	167.16
ST7052-3	3 dB	208.95	194.32	179.70	167.16
ST7052-6	6 dB	208.95	194.32	179.70	167.16
ST7052-10	10 dB	208.95	194.32	179.70	167.16
ST7052-20	20 dB	208.95	194.32	179.70	167.16
ST7052-30	30 dB	208.95	194.32	179.70	167.16

10 WATT, DC TO 18 GHZ TNC ATTENUATORS


IMSTDANCE: 50 Ohms
 ACCURACY: 1 THRU 6 dB, $\pm .5$ dB
 10 AND 20 dB, $\pm .7$ dB
 30 AND 40 dB, ± 1.5 dB
 VSWR: 1.40:1 MAXIMUM



Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7053-1	1 dB	\$313.45	\$291.51	\$269.57	\$250.76
ST7053-2	2 dB	313.45	291.51	269.57	250.76
ST7053-3	3 dB	313.45	291.51	269.57	250.76
ST7053-6	6 dB	313.45	291.51	269.57	250.76
ST7053-10	10 dB	313.45	291.51	269.57	250.76
ST7053-20	20 dB	313.45	291.51	269.57	250.76
ST7053-30	30 dB	313.45	291.51	269.57	250.76
ST7053-40	40 dB	344.80	320.66	296.53	275.84

25 WATT, DC TO 18 GHZ TNC ATTENUATORS


IMSTDANCE: 50 Ohms
 ACCURACY: 1 THRU 6 dB, $\pm .8$ dB
 10 AND 20 dB, ± 1.0 dB
 30 AND 40 dB, ± 2.0 dB
 VSWR: 1.40:1 MAXIMUM



Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7054-1	1 dB	\$449.30	\$417.85	\$386.40	\$359.44
ST7054-2	2 dB	449.30	417.85	386.40	359.44
ST7054-3	3 dB	449.30	417.85	386.40	359.44
ST7054-6	6 dB	449.30	417.85	386.40	359.44
ST7054-10	10 dB	449.30	417.85	386.40	359.44
ST7054-20	20 dB	449.30	417.85	386.40	359.44
ST7054-30	30 dB	449.30	417.85	386.40	359.44
ST7054-40	40 dB	470.20	437.29	404.37	376.16

50 WATT, DC TO 18 GHZ TNC ATTENUATORS


IMSTDANCE: 50 Ohms
 ACCURACY: 6 AND 10 dB, ± 1.0 dB
 20 AND 30 dB, ± 1.5 dB
 40 dB, ± 2.0 dB
 VSWR: 1.45:1 MAXIMUM



Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7055-6	6 dB	\$522.45	\$485.88	\$449.31	\$417.96
ST7055-10	10 dB	522.45	485.88	449.31	417.96
ST7055-20	20 dB	522.45	485.88	449.31	417.96
ST7055-30	30 dB	522.45	485.88	449.31	417.96
ST7055-40	40 dB	543.35	505.32	467.28	434.68

100 WATT, DC TO 1.5 GHZ TNC ATTENUATORS


IMSTDANCE: 50 Ohms
 ACCURACY: 6 dB, $\pm .8$ dB
 10 AND 20 dB, ± 1.0 dB
 30 AND 40 dB, ± 2.0 dB
 VSWR: 1.40:1 MAXIMUM



Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7056-6	6 dB	\$626.95	\$583.06	\$539.18	\$501.56
ST7056-10	10 dB	626.95	583.06	539.18	501.56
ST7056-20	20 dB	626.95	583.06	539.18	501.56
ST7056-30	30 dB	626.95	583.06	539.18	501.56
ST7056-40	40 dB	647.85	602.50	557.15	518.28

5 WATT, DC TO 7.5 GHZ 7/16 ATTENUATORS


IMSTDANCE: 50 Ohms
 ACCURACY: 1 THRU 6 dB, $\pm .4$ dB
 10 AND 20 dB, $\pm .6$ dB
 30 AND 40 dB, ± 1.5 dB
 VSWR: 1.25:1 MAXIMUM



Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7039-1	1 dB	\$156.70	\$145.73	\$134.76	\$125.36
ST7039-2	2 dB	156.70	145.73	134.76	125.36
ST7039-3	3 dB	156.70	145.73	134.76	125.36
ST7039-6	6 dB	156.70	145.73	134.76	125.36
ST7039-10	10 dB	156.70	145.73	134.76	125.36
ST7039-20	20 dB	156.70	145.73	134.76	125.36
ST7039-30	30 dB	156.70	145.73	134.76	125.36
ST7039-40	40 dB	177.60	165.17	152.74	142.08

10 WATT, DC TO 7.5 GHZ 7/16 ATTENUATORS


IMSTDANCE: 50 Ohms
 ACCURACY: 1 THRU 6 dB, $\pm .6$ dB
 10 AND 20 dB, $\pm .8$ dB
 30 AND 40 dB, ± 1.5 dB
 VSWR: 1.30:1 MAXIMUM



Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7040-1	1 dB	\$229.85	\$213.76	\$197.67	\$183.88
ST7040-2	2 dB	229.85	213.76	197.67	183.88
ST7040-3	3 dB	229.85	213.76	197.67	183.88
ST7040-6	6 dB	229.85	213.76	197.67	183.88
ST7040-10	10 dB	229.85	213.76	197.67	183.88
ST7040-20	20 dB	229.85	213.76	197.67	183.88
ST7040-30	30 dB	229.85	213.76	197.67	183.88
ST7040-40	40 dB	250.75	233.20	215.65	200.60

25 WATT, DC TO 7.5 GHZ 7/16 ATTENUATORS


IMSTDANCE: 50 Ohms
 ACCURACY: 1 THRU 6 dB, $\pm .4$ dB
 10 AND 20 dB, $\pm .6$ dB
 30 AND 40 dB, ± 1.5 dB
 VSWR: DC-4GHz 1.25 MAX
 4-7.5 GHz 1.45 MAX



Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7041-1	1 dB	\$365.70	\$340.10	\$314.50	\$292.56
ST7041-2	2 dB	365.70	340.10	314.50	292.56
ST7041-3	3 dB	365.70	340.10	314.50	292.56
ST7041-6	6 dB	365.70	340.10	314.50	292.56
ST7041-10	10 dB	365.70	340.10	314.50	292.56
ST7041-20	20 dB	365.70	340.10	314.50	292.56
ST7041-30	30 dB	365.70	340.10	314.50	292.56
ST7041-40	40 dB	386.60	359.54	332.48	309.28

50 WATT, DC TO 7.5 GHZ 7/16 ATTENUATORS


IMSTDANCE: 50 Ohms
 ACCURACY: 6 AND 10 dB, ± 1.0 dB
 20 AND 30 dB, ± 1.5 dB
 40 dB, ± 2.0 dB
 VSWR: 1.40:1 MAXIMUM



Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7042-6	6 dB	\$417.95	\$388.69	\$359.44	\$334.36
ST7042-10	10 dB	417.95	388.69	359.44	334.36
ST7042-20	20 dB	417.95	388.69	359.44	334.36
ST7042-30	30 dB	417.95	388.69	359.44	334.36
ST7042-40	40 dB	417.95	388.69	359.44	334.36

100 WATT, DC TO 1.5 GHZ 7/16 ATTENUATORS

IMSTDANCE: 50 Ohms
 ACCURACY: 6 dB, $\pm .5$ dB
 10, 20 & 30 dB, $\pm .75$ dB
 40 dB, ± 1.0 dB
 VSWR: 1.25:1 MAXIMUM



Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7043-6	6 dB	\$470.20	\$437.29	\$404.37	\$376.16
ST7043-10	10 dB	470.20	437.29	404.37	376.16
ST7043-20	20 dB	470.20	437.29	404.37	376.16
ST7043-30	30 dB	470.20	437.29	404.37	376.16
ST7043-40	40 dB	470.20	437.29	404.37	376.16