


DC TO 2 GHZ BNC ATTENUATORS

IMSTDANCE: 50 Ohms
 ACCURACY: 1 GHz, $\pm .5$ dB
 2 GHz, $\pm .8$ dB
 VSWR: 1 GHz, 1.20:1 MAXIMUM
 2 GHz, 1.40:1 MAXIMUM




AVERAGE POWER HANDLING CAPABILITY: 1 WATT

Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7000-1	1 dB	\$31.30	\$29.11	\$26.92	\$25.04
ST7000-2	2 dB	31.30	29.11	26.92	25.04
ST7000-3	3 dB	31.30	29.11	26.92	25.04
ST7000-6	6 dB	31.30	29.11	26.92	25.04
ST7000-10	10 dB	29.95	27.85	25.76	23.96
ST7000-20	20 dB	29.95	27.85	25.76	23.96
ST7000-30	30 dB	41.75	38.83	35.91	33.40

DC TO 4 GHZ BNC ATTENUATORS

IMSTDANCE: 50 Ohms
 ACCURACY: 1 THRU 6 dB, $\pm .4$ dB
 10 AND 20 dB, $\pm .6$ dB
 30 dB, $\pm .8$ dB
 VSWR: 1.25:1 MAXIMUM




AVERAGE POWER HANDLING CAPABILITY: 2 WATTS

Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7049-1	1 dB	\$73.10	\$67.98	\$62.87	\$58.48
ST7049-2	2 dB	73.10	67.98	62.87	58.48
ST7049-3	3 dB	73.10	67.98	62.87	58.48
ST7049-6	6 dB	73.10	67.98	62.87	58.48
ST7049-10	10 dB	73.10	67.98	62.87	58.48
ST7049-20	20 dB	73.10	67.98	62.87	58.48
ST7049-30	30 dB	73.10	67.98	62.87	58.48

10 WATT, BNC ATTENUATORS


IMSTDANCE: 50 Ohms
 FREQUENCY RANGE: DC TO 2,000 MHz
 ACCURACY: 1,000 MHz, $\pm .6$ dB
 2,000 MHz, ± 1.0 dB
 VSWR: 1,000 MHz, 1.30:1 MAXIMUM
 2,000 MHz, 1.60:1 MAXIMUM



Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7025-2	2 dB	\$198.50	\$184.61	\$170.71	\$158.80
ST7025-3	3 dB	198.50	184.61	170.71	158.80
ST7025-6	6 dB	198.50	184.61	170.71	158.80
ST7025-10	10 dB	198.50	184.61	170.71	158.80
ST7025-20	20 dB	198.50	184.61	170.71	158.80
ST7025-30	30 dB	198.50	184.61	170.71	158.80
ST7025-40	40 dB	229.85	213.76	197.67	183.88

100 WATT, BNC ATTENUATORS


IMSTDANCE: 50 Ohms
 FREQUENCY RANGE: DC TO 1 GHz
 ACCURACY: 3 & 6 $\pm .5$ dB
 10, 20 & 30 $\pm .75$ dB
 40 ± 1.0 dB
 VSWR: 1.40:1 MAXIMUM



Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7026-3	3 dB	\$574.70	\$534.47	\$494.24	\$459.76
ST7026-6	6 dB	574.70	534.47	494.24	459.76
ST7026-10	10 dB	574.70	534.47	494.24	459.76
ST7026-20	20 dB	574.70	534.47	494.24	459.76
ST7026-30	30 dB	574.70	534.47	494.24	459.76
ST7026-40	40 dB	622.75	579.16	535.57	498.20

75 OHM F ATTENUATORS


FREQUENCY RANGE: DC TO 1,000 MHz
 ACCURACY: $\pm .5$ dB
 VSWR: 1.30:1 MAXIMUM
 AVERAGE POWER HANDLING CAPABILITY: 2 WATTS



Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7057-1	1 dB	\$67.85	\$63.10	\$58.35	\$54.28
ST7057-2	2 dB	67.85	63.10	58.35	54.28
ST7057-3	3 dB	67.85	63.10	58.35	54.28
ST7057-6	6 dB	67.85	63.10	58.35	54.28
ST7057-10	10 dB	67.85	63.10	58.35	54.28

DC TO 1 GHZ 75 OHM BNC ATTENUATORS

ACCURACY: $\pm .6$ dB
 VSWR: 1.30:1 MAXIMUM




AVERAGE POWER HANDLING CAPABILITY: 1 WATT

Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7009-1	1 dB	\$36.50	\$33.95	\$31.39	\$29.20
ST7009-2	2 dB	36.50	33.95	31.39	29.20
ST7009-3	3 dB	36.50	33.95	31.39	29.20
ST7009-6	6 dB	36.50	33.95	31.39	29.20
ST7009-10	10 dB	36.50	33.95	31.39	29.20
ST7009-20	20 dB	36.50	33.95	31.39	29.20
ST7009-30	30 dB	36.50	33.95	31.39	29.20

DC TO 4 GHZ 75 OHM BNC ATTENUATORS

ACCURACY: 1 THRU 6 dB, $\pm .4$ dB
 10 AND 20 dB, $\pm .6$ dB
 30 dB, $\pm .8$ dB
 VSWR: 1.35:1 MAXIMUM




AVERAGE POWER HANDLING CAPABILITY: 2 WATTS

Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7050-1	1 dB	\$94.00	\$87.42	\$80.84	\$75.20
ST7050-2	2 dB	94.00	87.42	80.84	75.20
ST7050-3	3 dB	94.00	87.42	80.84	75.20
ST7050-6	6 dB	94.00	87.42	80.84	75.20
ST7050-10	10 dB	94.00	87.42	80.84	75.20
ST7050-20	20 dB	94.00	87.42	80.84	75.20
ST7050-30	30 dB	94.00	87.42	80.84	75.20

PLEASE CONTACT OUR ENGINEERING
 DEPARTMENT FOR ALL YOUR SSTCIAL
 REQUIREMENTS AT (949) 261-1920.

DC TO 1 GHZ 75 OHM N ATTENUATORS

ACCURACY: $\pm .6$ dB
 VSWR: 1.30:1 MAXIMUM
 AVERAGE POWER HANDLING CAPABILITY: 1 WATT




Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7029-1	1 dB	\$52.20	\$48.55	\$44.89	\$41.76
ST7029-2	2 dB	52.20	48.55	44.89	41.76
ST7029-3	3 dB	52.20	48.55	44.89	41.76
ST7029-6	6 dB	52.20	48.55	44.89	41.76
ST7029-10	10 dB	52.20	48.55	44.89	41.76
ST7029-20	20 dB	52.20	48.55	44.89	41.76
ST7029-30	30 dB	52.20	48.55	44.89	41.76

*WARNING: WILL NOT MATE TO 50 OHM N CONNECTORS

DC TO 4 GHZ 75 OHM N ATTENUATORS

ACCURACY: 1 THRU 6 dB, $\pm .4$ dB
 10 AND 20 dB, $\pm .6$ dB
 30 dB, $\pm .8$ dB
 VSWR: 1.30:1 MAXIMUM



AVERAGE POWER HANDLING CAPABILITY: 2 WATTS

Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7044-1	1 dB	\$104.45	\$97.14	\$89.83	\$83.56
ST7044-2	2 dB	104.45	97.14	89.83	83.56
ST7044-3	3 dB	104.45	97.14	89.83	83.56
ST7044-6	6 dB	104.45	97.14	89.83	83.56
ST7044-10	10 dB	104.45	97.14	89.83	83.56
ST7044-20	20 dB	104.45	97.14	89.83	83.56
ST7044-30	30 dB	104.45	97.14	89.83	83.56

*WARNING: WILL NOT MATE TO 50 OHM N CONNECTORS

