



COAX SURGE PROTECTOR

SSTCIFICATIONS

FREQUENCY RANGE: DC - 3 GHz
 INSERTION LOSS: .5 dB
 IMSTDANCE: 50 OHMS
 DC BLOCKING: NONE. WILL PASS DC FOR POWER AND CONTROL PURPOSES.
 MAX DC OR STAK AC IS 150 V
 FIRING POINT: 350 V $\pm 15\%$ @ < 100V/S > 1000 @ 5kv/ μ s RISE
 BREAKDOWN VOLTAGE: 20 TO 30V
 SURGE CURRENT: 5000 A (8/20 μ s PULSE)
 PLUG LIFE: >600 TIMES @ 500A PULSE (FIELD REPLACEABLE)




Model No.	POWER HANDLING	CONNECTOR TYST	PRICE			
	WATTS		1-24	25-49	50-99	100 +
ST7301-1	200	N FEMALE	\$94.00	\$87.42	\$80.84	\$75.20
ST7301-2	2000	N FEMALE	104.45	97.14	89.83	83.56
ST7301-3	200	N FEMALE BULKHEAD	110.75	103.00	95.25	88.60
ST7301-4	2000	N FEMALE BULKHEAD	110.75	103.00	95.25	88.60
REPLACEMENT CARTRIDGE			CARTRIDGE FOR			
ST7301-200CART	200		14.60	13.58	12.56	11.68
ST7301-2000CART	2000		14.60	13.58	12.56	11.68

MANUAL COAX SWITCH WITH SURGE PROTECTOR

SSTCIFICATIONS


FREQUENCY RANGE: DC - 1.3 GHz
 VSWR: 1.6:1 MAX
 INSERTION LOSS: .75 dB
 ISOLATION: 50 dB
 POWER HANDLING: 1500 WATTS RF
 IMSTDANCE: 50 OHMS
 CONNECTOR TYST: N FEMALE
 REPLACEABLE CARTRIDGE
 SWITCHING FUNCTIONS: WHEN THE KNOB POINTS TO THE CENTER (GROUND) SWITCH POSITION ALL ANTENNA CIRCUITS ARE INTERNALLY DISCONNECTED AND GROUNDED. WHEN THE KNOB IS IN AN ACTIVE POSITION THE UNUSED ANTENNA PORTS ARE GROUNDED. THE ACTIVE POSITION CIRCUIT IS CONTINUOUSLY PROTECTED BY THE REPLACEABLE CARTRIDGE.



MODEL NO.	NUMBER OF OUTPUT PORTS	PRICE			
		1-24	25-49	50-99	100 +
ST7139	2	\$146.25	\$136.01	\$125.78	\$117.00
ST7140	4	167.15	155.45	143.75	133.72
REPLACEMENT CARTRIDGE		CARTRIDGE FOR			
ST7139-CART		15.25	14.18	13.12	12.20

N FUSE HOLDERS

IMSTDANCE: 50 OHMS
 FREQUENCY RANGE: DC TO 1,000 MHz
 VSWR: 1.50:1 MAXIMUM
 FUSE LEVEL: 1/16 AMP = +23 dBm
 1/8 AMP = +29 dBm
 1/4 AMP = +35 dBm



Model No.	FUSE ELEMENT	PRICE			
		1-24	25-49	50-99	100 +
ST7300-1	1/16 AMP	\$75.30	\$70.03	\$64.76	\$60.24
ST7300-2	1/8 AMP	75.30	70.03	64.76	60.24
ST7300-3	1/4 AMP	75.30	70.03	64.76	60.24

A / B COAXIAL SWITCHES

FREQUENCY RANGE:DC TO 1,000 MHz
 VSWR:1.60:1 MAXIMUM
 INSERTION LOSS:70 dB MAXIMUM
 ISOLATION:50 dB MINIMUM
 POWER HANDLING CAPACITY:5 WATTS CW, COMMON TO SWITCHED PORTS
 (SWITCHED PORTS TERMINATED), 1/2 WATT SWITCHED PORTS TO COMMON SWITCHING TIME, 15 MILLISECONDS
 OSTRATING VOLTAGE (ACTUATED TO "B" POSITION):+12 VDC AT 45mA MAXIMUM
 OSTRATING TEMSTRATURE RANGE:-20°C TO +60°C

MODEL NO.	CONNECTOR TYST	IMSTDANCE	PRICE			
			1-24	25-49	50-99	100 +
ST7100	BNC FEMALE	50 OHMS	\$239.95	\$223.15	\$206.36	\$191.96
ST7101	75 OHM BNC FEMALE	75 OHMS	412.15	383.30	354.45	329.72
ST7102	N FEMALE	50 OHMS	261.20	242.92	224.63	208.96
ST7103	75 OHM N FEMALE	75 OHMS	219.45	204.09	188.73	175.56

