


10 WATT, DC TO 12.4 GHZ N ATTENUATORS

IMSTDANCE: 50 Ohms
 ACCURACY: 1 THRU 6 dB, $\pm .3$ dB
 10 AND 20 dB, $\pm .5$ dB
 30 AND 40 dB, ± 1.5 dB
 VSWR: 1:30:1 MAX



Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7048-1	1 dB	\$240.30	\$223.48	\$206.66	\$192.24
ST7048-2	3 dB	240.30	223.48	206.66	192.24
ST7048-3	6 dB	240.30	223.48	206.66	192.24
ST7048-6	10 dB	240.30	223.48	206.66	192.24
ST7048-10	20 dB	240.30	223.48	206.66	192.24
ST7048-20	30 dB	240.30	223.48	206.66	192.24
ST7048-30	40 dB	240.30	223.48	206.66	192.24
ST7048-40	40 dB	261.20	242.92	224.63	208.96

10 WATT, DC TO 18 GHZ N ATTENUATORS

IMSTDANCE: 50 Ohms
 ACCURACY: 1 THRU 6 dB, $\pm .5$ dB
 10 AND 20 dB, $\pm .7$ dB
 30 AND 40 dB, ± 1.5 dB
 VSWR: 1.40:1 MAXIMUM



Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7015-1	1 dB	\$261.20	\$242.92	\$224.63	\$208.96
ST7015-2	3 dB	261.20	242.92	224.63	208.96
ST7015-3	6 dB	261.20	242.92	224.63	208.96
ST7015-6	10 dB	261.20	242.92	224.63	208.96
ST7015-10	20 dB	266.40	247.75	229.10	213.12
ST7015-20	30 dB	266.40	247.75	229.10	213.12
ST7015-30	40 dB	266.40	247.75	229.10	213.12
ST7015-40	40 dB	282.10	262.35	242.61	225.68

25 WATT, DC TO 18 GHZ N ATTENUATORS


IMSTDANCE: 50 Ohms
 ACCURACY: 1 THRU 6 dB, $\pm .8$ dB 10
 AND 20 dB, ± 1.0 dB 30
 AND 40 dB, ± 2.0 dB
 VSWR: 1.40:1 MAXIMUM



Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7017-1	1 dB	\$365.70	\$340.10	\$314.50	\$292.56
ST7017-2	3 dB	365.70	340.10	314.50	292.56
ST7017-3	6 dB	365.70	340.10	314.50	292.56
ST7017-6	10 dB	365.70	340.10	314.50	292.56
ST7017-10	20 dB	365.70	340.10	314.50	292.56
ST7017-20	30 dB	365.70	340.10	314.50	292.56
ST7017-30	40 dB	365.70	340.10	314.50	292.56
ST7017-40	40 dB	417.95	388.69	359.44	334.36

50 WATT, DC TO 18 GHZ N ATTENUATORS


IMSTDANCE: 50 Ohms
 ACCURACY: 6 AND 10 dB, ± 1.0 dB
 20 AND 30 dB, ± 1.5 dB
 40 dB, ± 2.0 dB
 VSWR: 1.45:1 MAXIMUM



Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7019-6	6 dB	\$417.95	\$388.69	\$359.44	\$334.36
ST7019-10	10 dB	417.95	388.69	359.44	334.36
ST7019-20	20 dB	417.95	388.69	359.44	334.36
ST7019-30	30 dB	426.30	396.46	366.62	341.04
ST7019-40	40 dB	470.20	437.29	404.37	376.16

100 WATT, DC TO 1.5 GHZ N ATTENUATORS

IMSTDANCE: 50 Ohms
 ACCURACY: 6 dB, $\pm .5$ dB
 10, 20 & 30 dB, $\pm .75$ dB
 40 dB, ± 1.0 dB
 VSWR: 1.25:1 MAXIMUM



Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7021-6	6 dB	\$522.45	\$485.88	\$449.31	\$417.96
ST7021-10	10 dB	522.45	485.88	449.31	417.96
ST7021-20	20 dB	522.45	485.88	449.31	417.96
ST7021-30	30 dB	522.45	485.88	449.31	417.96
ST7021-40	40 dB	574.70	534.47	494.24	459.76

300 WATT, N ATTENUATORS

IMSTDANCE: 50 Ohms
 FREQUENCY RANGE: DC TO 1 GHz
 ACCURACY: $\pm .75$ dB
 VSWR: 1.40:1 MAXIMUM
 RF INPUT POWER: 300 WATT AVERAGE AT 25°C
 DERATED TO 75 WATTS AT 85°C



Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7031-1	1 dB	\$1353.25	\$1258.52	\$1163.80	\$1082.60
ST7031-2	2 dB	1353.25	1258.52	1163.80	1082.60
ST7031-3	3 dB	1353.25	1258.52	1163.80	1082.60
ST7031-6	6 dB	1353.25	1258.52	1163.80	1082.60
ST7031-10	10 dB	1353.25	1258.52	1163.80	1082.60
ST7031-20	20 dB	1353.25	1258.52	1163.80	1082.60
ST7031-30	30 dB	1353.25	1258.52	1163.80	1082.60

500 WATT, N ATTENUATORS


IMSTDANCE: 50 Ohms
 FREQUENCY RANGE: DC TO 500 MHz
 ACCURACY: $\pm .5$ dB
 VSWR: 1.15:1 MAXIMUM
 RF INPUT POWER: 500 WATT AVERAGE AT 25°C
 DERATED TO 250 WATTS AT 100°C



Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7032-1	1 dB	\$1567.45	\$1457.73	\$1348.01	\$1253.96
ST7032-2	2 dB	1567.45	1457.73	1348.01	1253.96
ST7032-3	3 dB	1567.45	1457.73	1348.01	1253.96
ST7032-6	6 dB	1567.45	1457.73	1348.01	1253.96
ST7032-10	10 dB	1567.45	1457.73	1348.01	1253.96
ST7032-20	20 dB	1567.45	1457.73	1348.01	1253.96
ST7032-30	30 dB	1567.45	1457.73	1348.01	1253.96

DC TO 2 GHZ TNC ATTENUATORS

IMSTDANCE: 50 OHMS
 ACCURACY: 1 GHz, $\pm .5$ dB
 2 GHz, $\pm .8$ dB
 VSWR: 1 GHz, 1.20:1 MAXIMUM
 2 GHz, 1.40:1 MAXIMUM




AVERAGE POWER HANDLING CAPABILITY: 1 WATT

Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7003-1	1 dB	\$46.95	\$43.66	\$40.38	\$37.56
ST7003-2	3 dB	46.95	43.66	40.38	37.56
ST7003-3	6 dB	46.95	43.66	40.38	37.56
ST7003-6	10 dB	46.95	43.66	40.38	37.56
ST7003-10	20 dB	46.95	43.66	40.38	37.56
ST7003-20	30 dB	46.95	43.66	40.38	37.56
ST7003-30	40 dB	46.95	43.66	40.38	37.56
ST7003-40	40 dB	67.85	63.10	58.35	54.28

DC TO 12.4 GHZ TNC ATTENUATORS


IMSTDANCE: 50 OHMS
 ACCURACY: 1 THRU 6 dB, $\pm .3$ dB
 10 AND 20 dB, $\pm .5$ dB
 30 AND 40 dB, ± 1.5 dB
 VSWR: 1.25:1 MAXIMUM
 AVERAGE POWER HANDLING CAPABILITY: 2 WATTS



Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7051-1	1 dB	\$94.00	\$87.42	\$80.84	\$75.20
ST7051-2	3 dB	94.00	87.42	80.84	75.20
ST7051-3	6 dB	94.00	87.42	80.84	75.20
ST7051-6	10 dB	94.00	87.42	80.84	75.20
ST7051-10	20 dB	94.00	87.42	80.84	75.20
ST7051-20	30 dB	94.00	87.42	80.84	75.20
ST7051-30	40 dB	94.00	87.42	80.84	75.20
ST7051-40	40 dB	114.90	106.86	98.81	91.92

DC TO 18 GHZ TNC ATTENUATORS

IMSTDANCE: 50 Ohms
 ACCURACY: 1 THRU 6 dB, $\pm .3$ dB
 10 AND 20 dB, $\pm .5$ dB
 30 dB, ± 1.5 dB
 VSWR: 1.35:1 MAXIMUM
 AVERAGE POWER HANDLING CAPABILITY: 2 WATTS



Model No.	ATTENUATION	1-24	25-49	50-99	100 +
ST7030-1	1 dB	\$188.05	\$174.89	\$161.72	\$150.44
ST7030-2	3 dB	188.05	174.89	161.72	150.44
ST7030-3	6 dB	188.05	174.89	161.72	150.44
ST7030-6	10 dB	188.05	174.89	161.72	150.44
ST7030-10	20 dB	188.05	174.89	161.72	150.44
ST7030-20	30 dB	188.05	174.89	161.72	150.44
ST7030-30	40 dB	188.05	174.89	161.72	150.44

