


SINGLE STAGE BENCH MOUNT ROTARY ATTENUATORS





ALL UNITS HAVE 1 WATT AVERAGE POWER,
1000 WATTS STAK, AND -20° C to 85° C
OSTRATING TEMSTRATURE.

MODEL NO.	FREQUENCY RANGE	IMSTDANCE	CONNECTORS	ATTENUATION RANGE	ATTENUATION ACCURACY OVERALL	VSWR (MAX)	PRICE			
							1-24	25-49	50-99	100 +
ST7034-1	DC-1	50 OHMS	BNC	0-1 dB in .1 dB steps	±.05 dB	1.20:1	\$292.55	\$272.07	\$251.59	\$234.04
ST7034-2	GHZ DC-	50 OHMS	FEMALE	0-100 dB in 10 dB steps	±.5 dB or 2%	1.20:1	365.70	340.10	314.50	292.56
ST7034-3	1 GHz	50 OHMS	BNC	0-10 dB in 1 dB steps	±.4 dB	DC-1 GHz @ 1.20:1 1-2 GHz @ 1.40:1	289.95	269.65	249.36	231.96
ST7034-4	DC-2 GHz	50 OHMS	BNC FEMALE	0-70 dB in 10 dB steps	±.5 dB or 3%	DC-1 GHz @ 1.20:1 1-2 GHz @ 1.40:1	344.80	320.66	296.53	275.84
ST7034	DC-2 GHz	50	BNC FEMALE	0-100 dB in 10 dB steps	±.5 dB or 3%	DC-1 GHz @ 1.30:1 1-2 GHz @ 1.50:1	490.3	456.0	421.7	392.28
-5	DC-2 GHz	OHMS	FEMALE	0-1 dB in .1 dB steps	±.05 dB	1.30:1	5	3	0	275.84
ST7034	DC-500 MHz	50	BNC	0-1 dB in .1 dB steps	±.05 dB	1.30:1	344.8	320.6	296.5	250.76
-6	DC-500 MHz	OHMS	FEMALE	0-10 dB in 1 dB steps	±.25 dB	1.30:1	0	6	3	250.76
ST7035	DC-500 MHz	75	BNC	0-70 dB in 10 dB steps	±1.0 dB	1.30:1	313.4	291.5	269.5	250.76
ST7035-4	DC-1 GHz	75 OHMS	BNC FEMALE	0-10 dB in 1 dB steps	±.4 dB	DC-500 MHz @ 1.30:1 500 MHz - 1 GHz @ 1.40:1	323.15	300.53	277.91	258.52
ST7035-5	DC-1 GHz	75 OHMS	BNC FEMALE	0-1 dB in .1 dB steps	±.07 dB	DC-500 MHz @ 1.30:1 500 MHz - 1 GHz @ 1.40:1	323.15	300.53	277.91	258.52
ST7035	DC-26.5 GHz	50 OHMS	3.5mm FEMALE	0-9 dB in 1 dB steps	±.5 dB	DC-18 GHz @ 1.45:1 18-26.5 GHz @ 1.70:1	1771.25	1647.26	1523.28	1417.00

TWO & THREE STAGE BENCH MOUNT ROTARY ATTENUATORS

ALL UNITS HAVE 50 OHMS BNC FEMALE CONNECTORS,
1 WATT AVERAGE POWER, 1000 WATTS STAK,
AND -20° C TO 85° C OSTRATING TEMSTRATURE.



MODEL NO.	FREQUENCY RANGE	NO. OF STAGES	ATTENUATION RANGE	ATTENUATION ACCURACY OVERALL	VSWR (MAX)	PRICE			
						1-24	25-49	50-99	100 +
ST7033	DC-2 GHz	2	0-110 dB in 1 dB steps	±.5 dB or 3%	DC-1000 MHz @ 1.30:1 1000-1500 MHz @ 1.50:1 1500-2000 MHz @ 1.70:1	\$691.20	\$642.82	\$594.43	\$552.96
ST7033-2	DC-2 GHz	2	0-80 dB in 1 dB steps	±.5 dB or 3%	DC-1000 MHz @ 1.30:1 1000-1500 MHz @ 1.50:1 1500-2000 MHz @ 1.70:1	634.40	589.99	545.58	507.52
ST7058-1	DC-1 GHz	3	0-81 dB in .1 dB steps	DC-30 MHz 0-1 dB, ±.02 dB 1-10 dB, ±.1 dB 10-81 dB, ±.2 dB 30-500 MHz 0-1 dB, ±.04 dB 1-10 dB, ±.2 dB 10-81 dB, ±.5 dB 500-1000 MHz 0-1 dB, ±.06 dB 1-10 dB, ±.3 dB 10-81 dB, ±.8 dB	DC-30 MHz @ 1.10:1 30-500 MHz @ 1.50:1 500-1000 MHz @ 1.50:1	1267.80	1179.05	1090.31	1014.24

RF CONNECTOR



+91 7217885948

www.rfconnector.in

pradeep@rfconnector.in



www.rfconnector.in