








S. NO.	Products	PART NO.	DESCRIPTION	IMAGES
1	N M to N F BH Surge Arrestor	ST04SANMFBH06	Impedance - 50ohm Frequency - DC-6Ghz/3Ghz VSWR - 1.5 Type - Bulkhead Max. Power - 100watt Connector - N M/F Compliance - ROHS Temp. Range - - 45°C – +85 °C	
2	N F to N F BH Surge Arrestor	ST04SANFFBH06	Impedance - 50ohm Frequency - DC-6Ghz/3Ghz VSWR - 1.5 Type - Bulkhead Max. Power - 100watt Connector - N F/F Compliance - ROHS Temp. Range - - 45°C – +85 °C	
3	N M to N F Coaxial Lighting Surge Protector	ST04CLSPNMF06	Impedance - 50ohm Frequency - DC-3Ghz VSWR - 1.5 Type - Lighting Protector Discharge Volt - 230V Connector - N F/F Compliance - ROHS Temp. Range - - 45°C – +85 °C	
4	DIN M to DIN F Surge Arrestor	ST04SADINMF06	Impedance - 50ohm Frequency - DC-3Ghz VSWR - 1.5 Type - Bulkhead Max. Power - 100watt Connector - DIN M-F Compliance - ROHS Temp. Range - - 45°C – +85 °C	
5	TNC M to TNC F Surge Arrestor	ST04SATNCFBH06	Impedance - 50ohm Frequency - DC-3Ghz VSWR - 1.5 Type - Bulkhead Max. Power - 100watt Connector - TNC M-F Compliance - ROHS Temp. Range - - 45°C – +85 °C	
6	DIN M to DIN F T-Type Surge Arrestor	ST04SADINMFT06	Impedance - 50ohm Frequency - DC-3Ghz VSWR - 1.5 Type - T Type Max. Power - 100watt Connector - DIN M-F Compliance - ROHS Temp. Range - - 45°C – +85 °C	
7	RJ 45 DC Surge Supperss for SMM	200SSH	Dimensions: H 5.2" x W 5.0" x D1.7" H Space between mounting holes: 4.24" (108) Size of knockouts: 0.75" (19 mm) Internal Connectors: Screw Terminal 10 AWG to 22 AWG Max Voltage Input: 59 VDC Connector - RJ 45 Max Voltage Input: 59 VDC Operating Temperature: -40°C to +55°C (- 40°F to 131°F)	
8	RJ 45 DC Surge Supperss for SMM	ST04ETSPD5KA	Discharge Current : 5kA (Maximum) / 0.5kA (Normal) DC Spark-Over Voltage : 90V @ 100V/s Data Line Protection : RJ45 10/100/1000 Mbps @ All 4 Pairs Compliance : IEEE 802.3.af/at/bt Max Voltage Input: 59 VDC Connector - RJ 45 Operating Temperature : -40 to 90°C	