



FEMALE PRE-INSULATING JOINT

Subordinate categories: head and connector terminal


2 (AWG 22-16) Max Current: 1max = 10A

Model Item No	Nema TAD (mm)	B	d	Size Dimension (mm)			H	Color,
				D	L			
FDD1.25-110 (5)	0.5x2.5	3.8	3.8	1.7	19.0		5.0	Red Red
FDD1.25-110 (8)	0.8x2.8	3.8	3.8	1.7	19.0		5.0	
Lead section : 0.5-1.5 mm ² FDD1.25-187 (5)	0.5x4.75	5.6	3.8	1.7	19.0		5.0	
FDD1.25-187 (8)	0.8x4.75	5.6	3.8	1.7	19.0		5.0	
FDD1.25-250	0.5x5.2	6.5	3.8	1.7	20.0		5.0	
FDD1.25-250	0.8x0.8	7.4	3.8	1.7	21.0		5.0	



Lead section : 1.5-2.5 mm² (AWG 16-14) Max Current: 1max = 15A

Model Item No	Nema TAD (mm)	B	d	Size Dimension (mm)			H	Color,
				D	L			
FDD2-110 (5)	0.5x2.5	3.8	4.3	2.3	19.0		5.0	Blue Blue
FDD2-110 (8)	0.8x2.8	3.8	4.3	2.3	19.0		5.0	
FDD2-187 (5)	0.5x4.75	5.6	4.3	2.3	19.0		5.0	
FDD2-187 (8)	0.8x4.75	5.6	4.3	2.3	19.0		5.0	
FDD2-205	0.5x5.2	6.5	4.3	2.3	20.0		5.0	
FDD2-250	0.8x6.35	7.4	4.3	2.3	21.0		5.0	
FDD2-312	0.8x0.8	9.0	4.3	2.3	23.0		5.0	



Conductor cross-section : 4-6 mm² (AWG 12-10) Max Current: 1max = 24A

Model Item No	Nema TAD (mm)	B	d	Size Dimension (mm)			H	Color,
				D	L			
FDD5.5-250	0.8x6.35	7.4	5.7	3.4	25.0		13.0	Yellow
FDD5.5-375	1.2x9.4	10.9	5.7	3.4	29.6		13.0	Yellow

