




# Synergy Telecom P Ltd.

Synergy Telecom (P) Ltd **1.6/5.6 L L-9(F) R/A BT** Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd



## Electrical Specification

**Characteristic Impedance**

75 ohm

**Frequency Range**

DC-4 GHz

**VSWR**

≤ 1.23(0~2.2G)

**Dielectric strength**

≥25000V RMS, at sea level

**Dielectric Resistance**

≥ 10000 M Ω

**Insertion Loss**

≤ 0.08dB (@2200MHz)

**Center Contact Resistance**

≤ 10M Ω

**Outer Contact Resistance**

≤ 5MΩ

**RoHS**

Compliance

## Mechanical

**Durability Mating cycle**

≥500

**Termination cable retention**

≥300N

## Material Specification

**Connector Parts**

**Material**

**Plating**

**Body**

Brass

Gold/nickel

**Outer Contact**

Brass

CuSnZn

**Center Contact**

Brass

Au

**Fastener**

Brass

Ni

**Dielectric**

PTFE

-

## Environmental

**Temperature Range**

- 65°C – +155 °C

13-15 RPS flats, E-block, Vikaspuri, N Delhi-110018, India  
 Phone-91 11 28533349, Mobile-91 98101 38894, Fax -91 11 2853 1435,  
 E-mail : pradeep@rfconnectorhouse.com, Website : http://www.rfconnector.info/