

Fishfinder 160C

Physical & Performance:		
Unit dimensions, WxHxD:	6.1" x 4.9" x 2.9" (15.5 x 12.4 x 7.4 cm)	
Display size, WxH:	3.2" x 3.2" (8.0 x 8.0 cm)	
Display resolution, WxH:	128 x 128 pixels	
Display type:	16-color CSTN	
Weight:	17.6 oz (499 g)	
Waterproof:	yes (IPX7)	
Features:		
CANet® compatible:	no	
Audible alarms:	yes	
Dual-frequency sonar capable:	no	

Dual-beam sonar capable :	yes	
Split-screen zoom:	no	
Ultrascroll™ (displays fish targets at higher boat speeds):	yes	
See-thru® technology (exposes fish hidden in cover):	yes	
Fish Symbol ID (helps identify fish targets):	yes	
AutoGain Technology (minimizes clutter, maximizes targets):	yes	
Whiteline (indicates hard or soft bottom):	yes	
Adjustable depth line (measures depth of underwater objects):	no	
A-scope (real time display of fish passing through transducer beam):	no	
Bottom lock (shows return from the bottom up):	no	
Water temperature log and graph:	yes	
Water temperature sensor included:	no	
Water speed capable (displays speed on water):	yes	
Other:		

Frequency:	80/200 kHz (dual beam)
Transmit power:	150 W (RMS), 1200 W (peak to peak)
Voltage range:	10-18 VDC
Maximum depth:	900 ft
Cone angle:	45° or 15° (dual beam)