



SureFlex® Jumper with interface types N Male and DIN Male

SureFlex® Jumper with interface types N Male To DIN Male

| | |
|-------------------------|--------------|
| Body Style, Connector A | Straight |
| Body Style, Connector B | Straight |
| Cable Family | 1/2" S.F |
| Interface, Connector A | N Male |
| Interface, Connector B | DIN Male |
| Nominal Size | 1/2 in |
| Length | 4.5m 15 ft |

Specification Sheet Revision Level A

| | |
|------------------|-------------|
| 3rd Order IMD | -100.00 dBm |
| DTF, Connector A | -32.00 dB |
| DTF, Connector B | -32.00 dB |

| Frequency Band | VSWR | Return Loss (dB) | VSWR, typical | Return Loss, typical (dB) |
|----------------|------|------------------|---------------|---------------------------|
| 0-3000 MHz | | | 1.11 | 26.00 |
| 2.2-2.7 GHz | | | 1.08 | 28.00 |

| | | |
|---------------|------|-------|
| 698-960 MHz | 1.06 | 30.00 |
| 1700-2200 MHz | 1.06 | 30.00 |

Agency

RoHS 2011/65/EU
China RoHS SJ/T 11364-2006

Classification

Compliant by Exemption
Above Maximum Concentration Value (MCV)



Superflexible Foam Coaxial Cable, corrugated copper, 1/2 in, black PE jacket