

Synergy Telecom P Ltd.

Synergy Telecom (P) Ltd **ATTENUATOR 100W 15dB 3 GHz** (P) Ltd Synergy Telecom (P) Ltd

PART NO_ SYATF0C1503N1 Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd

Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd

Synergy Telecom (P) / Synergy Telecom (P) Ltd

Synergy Telecom (P) / Synergy Telecom (P) Ltd

Synergy Telecom (P) / Synergy Telecom (P) Ltd

Synergy Telecom (P) / Synergy Telecom (P) Ltd

Synergy Telecom (P) / Synergy Telecom (P) Ltd

Synergy Telecom (P) / Synergy Telecom (P) Ltd



Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd

Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd

Electrical Specification

Characteristic Impedance 50 ohm
Frequency Range 0~3000Mhz

Input VSWR ≤ 1.19

Output VSWR ≤ 1.29

Attenuation 15dB

Attenuation Accuracy ≤ 1.0 dB

IMD -110 dBc

Input Connector N male

Output Connector N female

Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd

RoHS Compliance

Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd

Environmental

Temperature Range - 33°C ~ +55 °C

Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd

13-15 RPS flats, E-block, Vikaspuri, N Delhi-110018, India
 Phone-91 11 28533349, Mobile-91 98101 38894, Fax -91 11 2853 1435,
 E-mail : pradeep@rfconnectorhouse.com, Website : http://www.rfconnector.info/