





SYNERGY TELECOM PVT LTD

13-15 RPS Flats, E-Block VIKASPURI N DELHI 110018... INDIA
 Phone-91 11 28533349, MOBILE 9810138894, FAX -91 1128531435,
 Email: - pkumar@ndb.vsnl.net.in , Web site: - www.rfconnector.info

Speicfication

| | |
|---|---|
|  | <p>Product Name:5Db directional coupler Frequency:800-2500 MHz Coupling Value: 5 ± 0.8 dB Insertion Loss: ≤ 2.0 dB Isolation: ≥ 25 dB VSWR: ≤ 1.25 Power Rating: 100W Connector:N-female Size: 156.6 mm×58.3 mm×18.5 mm</p> |
|  | <p>Product Name:7Db directional coupler Frequency:800-2500 MHz Coupling Value: 7 ± 0.8 dB Insertion Loss: ≤ 1.3dB Isolation: ≥ 27 dB VSWR: ≤ 1.25 Power Rating: 100W Connetor:N Female Size: 156.6 mm×58.3 mm×18.5 mm</p> |
|  | <p>Product Name:10 Db directional coupler Frequency: 800-2500 MHz Coupling Value: 10 ± 1.0 dB Insertion Loss: ≤ 0.75 dB Isolation: ≥ 30 dB VSWR: ≤ 1.25 Power Rating: 100W Connetor:N Female Size: 156.6 mm×58.3 mm×18.5 mm</p> |
|  | <p>Product Name:15 Db directional coupler Frequency: 800-2500 MHz Coupling Value: 15 ± 1.0 dB Insertion Loss: ≤ 0.3 dB Isolation: ≥ 35 dB VSWR: ≤ 1.25 Power Rating: 100W Connetor:N Female Size: 156.6 mm×58.3 mm×18.5mm</p> |