

Synergy Telecom P Ltd.

Din M DIN F T TYPE SURGE ARRESTOR



Electrical Specification

Characteristic Impedance	50 ohm
Frequency Range	800-2500 MHz
VSWR	<1.15
Insertion Loss	≤ 0.20DB
MAXIMUM IMPULSE DISCHARGE CURRENT	100KA

Material Specification

Connector Parts	Material	Plating
BODY	Brass	-
INSULETOR	TEFLON	NI
Center CONDUCTOR	PHOSPHOR BRONZE	Ag
O RING	SILICONRUBBER	-

Environmental

Temperature Range	- 40°C – +85 °C
--------------------------	-----------------

13-15 RPS flats, E-block, Vikaspuri, N Delhi-110018, India
 Phone-91 11 28533349, Mobile-91 98101 38894, Fax -91 11 2853 1435,
 E-mail : pradeep@rfconnectorhouse.com, Website : <http://www.rfconnector.info/>

Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd
Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd
Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd