

# SYNERGY TELECOM P. LTD.

Model	MHT-N5-2
Rated operating voltage	5VDC
Max continuous operating voltage	6VDC
Rated operating current	4ADC
Series resistance	0.5Ω±20%
Insulation resistance	≥1kΩ
Transmission frequency	1.2~2.6GHz
Exchange tolerance	0.25A(1s, 5 times)
Impact tolerance	4kV, 1.2/50μs; 2kA, 8/20μs(10 times)
Nominal discharge current	20kA(8/20μs)
Max discharge current	25kA (8/20μs)
Voltage protection level	≤15V(8/20μs, 20kA)
	≤20V(1.2/50μs ,4kV)
SPD type	1
Continuous power input RF	≤100W
Overload fault mode	Mode 3
Voltage standing wave ratio	≤1.12
Insertion loss	≤0.2dB
Port characteristic impedance	50Ω
Port model	N(F/M)
Waterproof level	IP67
max weight	300g



WZ-47 BUDDEHLLA VILLAGE, VIKAS PURI, NEW DELHI-110018  
 PHONE:- 011-28533349, MOB;-9810138894/9212558066, FAX:-01128533349  
 EMAIL:- [info@synergytpl.com](mailto:info@synergytpl.com) WEBSITE:- <http://rfconnector.in>