

Synergy Telecom P Ltd.

Synergy Telecom (P) Ltd **2 WAY CAVITY SPLITTER 700-3500MHZ** Synergy Telecom (P) Ltd

Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd

Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd

Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd

Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd

Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd

Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd

Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd



Electrical Specification

Characteristic Impedance	Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd	50 ohm
Frequency Range	Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd	700– 3500
VSWR	Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd	≤1.22
Insertion Loss	Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd	≤0.2
Amplitude Balance (dB)	Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd	≤ 0.5
Power	Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd	200watt
Connector	Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd	N-F
RoHS	Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd	Synergy Telecom (P) Ltd	Compliance

Material and plating:

Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd

- **Wide Band**
- **High Power Handling**
- **Low Insertion Loss**
- **Custom Design Available**

Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd Synergy Telecom (P) Ltd

Environmental

Temperature Range

- 30°C – +75 °C

WZ-47 BUDHELLA VILLAGE, VIKASPURI, NEW DELHI – 110018

PHONE: 011-28533349, MOB: 9810138894/9212558066, FAX: 011-28533349

EMAIL: info@rfconnector.in, WEBSITE: <http://rfconnector.in/>