


Synergy Telecom P Ltd.

14 AWG 2 CORE AUDIO SPEAKER CABLE



Applications: Audio Wire and Cable, Electrolytic Tough Pitch (ETP) High-Conductivity Copper Speaker Cables, Audio, Control and Instrumentation Cable

- Our speaker cables feature soft drawn and annealed conductors which result in greater flexibility without breakage
- Jackets are easy to strip, saving installation time and money

CONSTRUCTION

Conductor Material	Annealed bare Copper
Insulation Material:	PVC - Polyvinyl Chloride
Outer Shield Material:	Unshielded
Outer Jacket Material:	PVC - Polyvinyl Chloride
No. of Cores	2
Area of Cross Section	14 AWG

TECHNICAL

WORKING VOLTAGE	100V
WORKING VOLTAGE (CE)	450/750V
TEST VOLTAGE (AC)	2.5 kV for 5 MIN
CONDUCTOR RESISTANCE	< 9.8 Ω /KM
INSULATION RESISTANCE	> 200 M Ω .M
TEMPERATURE RATING	-0 to +70°C
(STATIC)OVERALL DIAMETER	7.5MM
BENDING RADIUS	15 X OD

APPEREANCE

COLOUR CODE	RED & BLACK
JACKET COLOUR	BLACK

PRINTING: RF CONNECTOR HOUSE 14 AWG 2 CORE AUDIO SPEAKER CABLE (SYASC14A02)

WZ-47 BUDHELLA VILLAGE, VIKASPURI, NEW DELHI – 110018
PHONE: 011-28533349, MOB: 9810138894/9212558066, FAX: 011-28533349
EMAIL: info@rfconnector.in, WEBSITE: <http://rfconnector.in/>