

Synergy Telecom P Ltd.

SP3T - Q3 Series
Open Ports Terminated
w/Mounting Bracket
DC - 26.5 GHz
Failsafe, Latching, Momentary



SPECIFICATIONS

FREQ. (GHz)	DC - 2.0	2.0-4.0	4.0-8.0	8.0-12.4	12.4-18.0	18.0-26.5
VSWR	1.20:1	1.20:1	1.25:1	1.30:1	1.40:1	1.50:1
INSERTION LOSS	0.20	0.20	0.25	0.30	0.40	0.60
ISOLATION	90	80	80	70	60	50
IMPEDANCE	50 Ohms					

MECHANICAL	
CONTACT	BREAK BEFORE MAKE
ACTUATOR	FAILSAFE, LATCHING, MOMENTARY
SWITCHING SPEED	20 mSEC MAX
ELECTRICAL	
ACTUATOR VOLTAGE	12.0, 15.0, 24.0, 28.0 Vdc
ACTUATOR CURRENT	VARIES UPON ACTUATOR VOLTAGE - CONTACT CEI
POWER HANDLING	200 WCW @ 1.0 GHz
TERMINATION	8 WATTS MAX.
ENVIRONMENTAL	

OPERATING TEMP	-40 DEG C TO 90 DEG C (STANDARD) -54 DEG C TO 90 DEG C (OPT /MS **)
SINE VIBRATION	30 G'S rms
LIFE	1,000,000 CYCLES
RANDOM VIBRATION	20 G'S rms
FINISH	
RF CAVITY	ALUMINUM, ELECTROLESS NICKEL PLATED PER MIL-C-26074, CLASS 4 UNLESS LOW OR ULTRA LOW PIM
ENCLOSURE	ALUMINUM, BLUE OR BLACK
CONTACT	BERYLLIUM COPPER, GOLD PLATED PER MIL-G-45204
CONNECTOR SHELL	CRES, PASSIVATED PER QQ-P-35 OR BRASS, ELECTROLESS NICKEL PLATED PER MIL-C-26074

13-15 RPS flats, E-block, Vikaspuri, N Delhi-110018, India
Phone-91 11 28533349, Mobile-91 98101 38894, Fax -91 11 2853 1435,
E-mail : pradeep@rfconnectorhouse.com, Website : <http://www.rfconnector.info/>