



PRODUCT DATA SHEET




TUV Rheinland

Solar PV Connector
 Pin dimensions:- $\phi 4.0\text{mm}$
 Suitable cable cross sections:-
 4mm^2 (20A), 6mm^2 (30A)
 IP-68 Grade



Basic Dimensions




Ordering Code:-

Solar PV Connector	Wire Type	Wire Color	Wire Stripping Length	Wire Length(L)
ESC-4-PM-M	A 4 Sq.mm	03 Black	8 8 mm	As per Customer Requirement
ESC-4-PM-F	B 6 Sq.mm	04 Red	10 10 mm	
		21 Black with Red strip		

Example:-

- Solar PV Connector without wire
ESC-4-PM-M ,ESC-4-PM-F
- Solar PV Connector with wire
ESC-4-PM-A-03-1meter.

Panel Cutout



Specification Table

SR.NO	PARAMETER	SPECIFICATION
1	Type	$\phi 4\text{mm}$ PV Connector
2	Rated current	20A(4sqmm)&30A(6sqmm)
3	Rated voltage	1500V DC
4	Test voltage	8000V AC(1min)
5	Typical contact Resistance	$\leq 0.35\text{mOhms}$
6	Degree of protection (Mated)	IP68(IEC 60529)
7	Protection class	II
8	Flammability class	UL94V-0
9	Insulation material	PPO
10	Contact material	Copper/Copper Alloy, Silver plated
11	Temperature range	$-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$
12	Upper limiting temperature	100°C
13	Cable size	2.5mm^2 , 4mm^2 & 6mm^2
14	Rated Impulse Voltage	10KV

SR.NO	PARAMETER	SPECIFICATION
15	Application Class	A
16	Pollution Degree	3
17	Over voltage category	Category III
18	Relative Humidity (%)	$85\% \pm 5\%$
19	Pin dimensions	$\phi 4.0\text{mm}$
20	Stripping Length	8 TO 10 mm.
21	Insertion force (male Female hsg.)	$\leq 50\text{N}$
22	Withdrawal force (male Female hsg.)	$\geq 190\text{N}$
23	Sealing Material	Silicon Rubber
24	Minimum Creepage Distance	Contact to contact not applicable
25	Insulation Resistance	$> 1000\ \text{M}\Omega$
26	Reference Standard	IEC 62852:2014
27	Approval	TUV

PRODUCT : SOLAR $\phi 4\text{mm}$ PV CONNECTOR PANEL MOUNTING TYPE						CODE : ESC-4-PM-X						
5	IEC 62852:2014	EN-50521:2008	17.03.17	Vicky	GJG	APP	30.03.16	GJG	Plot E-4, Kagal Five Star MIDC, Kagal, Kolhapur, MH - 416236, India Elcom International Pvt. Ltd.			
4	Rated voltage	1500V DC Added	28.10.16	Vicky	GJG	CHK						
3	Stripping Length	8 TO 10 mm.	21.10.16	Vicky	GJG	DRN	30.03.16	Sugar				
2	Stripping Length	8mm Max.										
2	Ordering code modified		21.04.16	Sugar	GJG	BY	DATE	SIGN				
REV	IS	WAS	DATE	SIGN	APP.	BY	DATE	SIGN				
UNSP.TOLERANCE			DIMNS. IN	WT(Gm)	SCALE:-	PROJECTION	SHEET	DRAWING NUMBER				
OVER	-	1	10	mm	Max.	NTS.						
UP TO	1	10	-	Moulding, plating details as per Bill of Material				1 OF 1	P E S C 2 1 1 1			REVISION
\pm	0.2	0.3	0.5	Unspecified colour is Black, GF:Glass filled.								