

# Synergy Telecom P Ltd.

## Pneumatic Shield Box



**Product name** :Pneumatic Shield Box(D3020)

**Product No.:**1075

**Applications:**For GSM,GPS,PHS,BLUETOOTH,WLAN tests

### **Specification:**

- ◆ Shielding effectiveness:  $\geq 75$ dB(0~3GHZ)
- ◆ Outer demensions:340(w)\*260(D)\*300(H)mm
- ◆ Inner demensions:290(w)\*180(D)\*135(H)mm
- ◆ Shielding material:absorbing rubber
- ◆ Operating temperature:0 ~ 50°C
- ◆ Storage temperature:-10 ~ 60°C
- ◆ RF connector:RS232\*1 PCS,SMA \*2PCS,DB-9PIN,DB-25PIN

**Accessories:**

Air pipe connector \*1 pcs

AC connector \*1pcs

Air pressure control valve \*6pcs

switch \*2pcs

Display lamp \*2pcs

**Power supply parameter**

Input voltage:220V AC

Consume current:<0.2A

Frequency:50/60Hz

Power :<15w

**Input air pressure parameter**

Input air pressure:5 ~ 10 Par

Air connector:outer diameter 6mm quick port

Air pipe :Diameter 4mm

13-15 RPS flats, E-block, Vikaspuri, N Delhi-110018, India  
Phone-91 11 28533349, Mobile-91 98101 38894, Fax -91 11 2853 1435,  
E-mail : pradeep@rfconnectorhouse.com, Website : <http://www.rfconnector.info/>